

i-TECH SIGNAGE LCD

the best solution for your advertising message



Item		FCHPC3200	FCHPC4200	
Display	LCD Panel	TFT LCD		
	Screen Size	32-inch 16:9	42-inch 16:9	
	Resolution	1280x768 (optional 1366x768)	1280x768 (optional 1920x1080)	
	Luminance(cd/m2)	550		
	Contrast Ratio	1200:1		
	Viewing Angles(H/V)	176°/176°	176°/176°	
	Response Times(ms)	6.5		
	OSD Language	English/German/French/Spanish/Italian		
General	Computing	Intel® Celeron® D / Pentium® 4		
	HDD	80GB		
	Memory	256MB DDR-400,(x4 184Pin DIMM Slots Support up to 2GB)		
	Wireless	802.11 b/g		
	LAN Module	LAN / WLAN / 3G: EVDO, UMTS, CDMA (Optional)		
	DVD ROM	Slim DVD COMBO		
	Interface	USB Port	x4 port	
		Network (LAN)	RJ-45x1 port	
		VGA out	x1 port (Optional)	
		Audio out	x1 port	
		Service	RS-232X1 (Optional)	
		AC input	x1	
		Card Bus	PCMCIA 32 Bit Card Bus	
Others	Power Source	AC100~240V 50~60Hz		
	Power Consumption	160W	230W	
	Touch Screen	(Optional)		
	Dimension(H x W x D)	814x510x136 mm	1040x632x136 mm	
	Weight	26.Kg(Net)	33.8Kg(Net)	
Mounting Bracket	Wall-mount Kit (Optional)			

※Design and specifications are subject to change without notice.

i-TECH SIGNAGE LCD

the best solution for your advertising message



FEATURES

- LAN/ WLAN/ 3G: EVDO / UMTS / CDMA
- Real-time update
- Plug and play
- Low power-consumption
- Multimedia and interactive
- Multi format input



available size: 32", 37", 42", 47"

REMOTE CONTROL PLATFORM FEATURES

- Centralize management from anywhere
- Remotely control all outlets in the world
- Manage and maintain playlist and artwork
- Auto log-in / real time update

SOLUTION

