

20.1" Outdoor Digital Signage, All Weather Proof LCD

i-Tech's IP65 All-Weather/OutDoor Full-Sun environment SunLight Retable LCD monitors that allow you to view the display under the full sunlight. These affordable solutions are ready to deploy to any indoor and outdoor digital signage application for retails stores, restaurants, gas stations and many more....

We produce the largest and brightest SunLight Readable LCD Monitor.



Technical specifications

Active area size (W x H)	20.1" (408x 306 mm)
Pixel pitch (mm)	0.51(H) x 0.51 (V)
Panel resolution (pixels)	800 x 600
Luminance of white	800 cd/m2 (Typ)
Contrast ratio	500:1
Response time (gtg)	16 ms (Typ)
Color Range	16.7 Million colors
Viewing angle	160(H) 120 (V) typ. with CR >10
Video inputs	VGA; S-Video
Auto Brightness Control	Yes
Front glass type	Optically bonded laminated AR glass
IP Class	IP65
Operating temperature range	-20C to +50C (Covered)
Storage Temperature	TBD
CCFL Life Time	60K hrs (min)
Input voltage	90 – 265 Vac
Power consumption	200 W (max)
Weight	25lb Note: VBSA100 Mounting
External dimensions (W x H x D)	470 x 375 x 110 mm Notes: to guarantee a proper Functionality, 10cm of clearance must be kept around the display
Portrait version	Please contact I-Tech for details
Available Accessories	IR Remote Control and VGA cable (included) Serial Cable and Ethernet Cable (not included)
Customization	Please contact I-Tech for available options