


Model: G-OD3200

32" Outdoor Digital Signage Sunlight All Weather Proof LCD

i-Tech's All-Weather/OutDoor Full-Sun environment SunLight Retable LCD monitors that allow you to view the display under the full sunlight. This affordable solutions are ready to deploy to any indoor and outdoor digital signage application for retails stores, restaurants, gas stations and many more....

We produce the largest and brightest SunLight Readable LCD Monitor in sizes from 32" to 65".



Technical specifications

Active area size (W x H)	32" (698 x 392 mm)
Pixel pitch (mm)	0.51075(H) x 0.51075 (V)
Panel resolution (pixels)	1366 x 768
Supported video resolutions	Customizable up to 1920x1080 @ 60Hz
Luminance of white	500 cd/m2 (Typ)
Contrast ratio	900:1 min. (dark room) ref MIL L 85xxxx
Response time (gtg)	12 ms (Typ)
Colour Range	16.7 Million colours (max)
Viewing angle	196(H) 196 (V) typ. with CR >10
Video inputs	DVI-D; VGA; S-Video; CVBS
Remote diagnostic functionalities (via RS232)	Yes
Auto Brightness Control	Yes
Front glass type	Optically bonded laminated AR glass (removable)
Impact Damage protection	EN356-P3A (Glass) IK-8 (Housing)
IP Class	IP65
Operating temperature range	-20C to +45C (Direct Sunlight) -20C to +50C (Covered)
Storage Temperature	TBD
Certifications	CE / cCSAus
RoHS	No. RphS version available Q1 2007
CCFL Life Time	60K hrs (min)
Input voltage	90 – 265 Vac
Power consumption	200 W (max)
Weight	65 Kg Note: 2 fixing points side by side are available for wall/stand mounting
External dimensions (W x H x D)	850 x 500 x 232 mm Notes: to guarantee a proper functionality, 10cm of clearance must be kept around the display
Portrait version	Please contact I-Tech for details
Available Accessories	IR Remote Control and VGA cable (included) Serial Cable and Ethernet Cable (not included)
Customization	Please contact I-Tech for available options