

17" open frame with 1000nits(typ.)brightness, 1280x1024 resolution, I/O:VGA/DVI/HDMI, power: 12/24V DC-in,RS232 command control and light sensor built-in, black painted metal chassis with ear mount and VESA mount accessory: VGA cable x 1, external light sensor cable x 1

Model: GOP1700HB

FEATURES:

- 17" LCD support SXGA resolution
- 1000 nits sunlight readable (with auto dimming)
- Multi video signal IO: VGA / DVI / HDMI
- Special 24/7 long term operation design
- Wide operation temperature range
- Built-in RS232 OSD command control

SPECIFICATIONS:

Function	Items	Description	Remark	
Display	Display area (mm)	337.920(H) × 270.336(V)	17" 5:4 diagonal	
	Brightness (nits)	1000 (typ.)	.	
	Optimum resolution	1280 x 1024		
	Contrast Ratio	1000:1		
	View angle (H/V)	170/160 degree		
	Backlight Life	30,000 hours (min)		
System	Video input	VGA / DVI / HDMI		
	Video output	NA		
	Audio output	Built-in	(Option)	
		Extend	(Option)	
	Memory	NA		
	Storage	NA		
	Ethernet	NA		
	Wireless	NA		
Touch panel	Type	NA		
	Protection glass	NA		
	Support OS	NA		
Special Control	Manual	(Option)		
	OSD	5 keys at back side		
	RS232	Yes	Video selection, ON/OFF etc	
	Display feedback	NA		
Power	Power Input voltage	DC 12V/24V		
	Consumption(W)	40 (typ)		
Mechanical	Outline (mm)	392 x 299 x 49 (D)		
	Mounting	Open frame bracket / 75x75 (mm) VESA		
	Others	NA		
Environment	Operating temp.	0~65 0C		
	Storage temperature	-10~65 0C		
	IP protection	NA		
	Anti-vandal	(TBD)		
	Auto brightness	Yes	By extension cable	
	TFT surface	AG		
	Certification	CE / FCC		

MECHANICAL DRAWINGS:

