

**23.8" Open Frame Monitor with 3000nits Brightness**  
 1920x1080 resolution, I/O:VGA/DVI/HDMI, power: 100~240V AC-in,  
 metal chassis with rear VESA mount and ear mount design, built-in  
 auto temperature and brightness control accessories: VGA cable x1,  
 light sensor cable x1, Rear mount brackets x4

**Model: GOPW2380HB3**

**FEATURES:**

- 23.8" LCD support 1920x1080 FHD resolution
- 3000 nits extreme high brightness
- 178/178 view angle free landscape / portrait directions
- Video signal IO: VGA / HDMI / DVI
- Special 24/7 long-term operation design
- Auto temperature / brightness control
- RS232 command control port
- Metal chassis with VESA / ear mount design

**SPECIFICATIONS:**

Function	Items	Description	Remark	
<b>Display</b>	Display area (mm)	527.04 (H) x 296.46 (V)	23.8" diagonal	
	Brightness (nits)	3000		
	Optimum resolution	1920 x 1080		
	Contrast Ratio	3000 :1		
	View angle	178 / 178 degree	In all direction	
	Backlight Life	50,000 hours		
<b>System</b>	Video input	VGA / HDMI / DVI		
	Video output	NA		
	Audio	Built-in	(Option)	2Wx2
		Extend	Line-out	
	Memory	NA		
	Storage	NA		
	Ethernet	NA		
	Wireless	NA		
<b>Special Control</b>	Manual	NA		
	OSD	5 keys on the back		
	RS232	YES		
	Display feedback	NA		
<b>Power</b>	Power Input voltage	AC 100-240 V		
	Consumption(W)	130 (typ.)		
<b>Mechanical</b>	Outline (mm)	575.60 x 354.51 x 53.0 (TBD)		
	Mounting	200 x 200/ 100 x 100 (mm) VESA		
	Others	NA		
<b>Environment</b>	Operating temp.	-10~50 °C	Auto temperature control	
	Storage temperature	-10~55 °C		
	IP protection	NA		
	Anti-vandal	NA		
	Auto brightness	YES	External light sensor cable	
	Direct sunlight	NA		
Certification	CE / FCC			

# MECHANICAL DRAWINGS:

