



42.5" Open Frame Monitor with 1000nits (typ.) Brightness, 1920x1080resolution, I/O: VGA/DVI/HDMI, power: 24V DC-in, metal chassis with rear VESA mount and ear mount design accessories: CGA cable x1, ear mount brackets x 4
Power consumption 150W for 24V DC-in

Model: GOPW4250HB1

FEATURES:

- 43" LCD support Full-HD resolution
- High brightness 1000 nits
- IPS extra wide view angle, Hi-Tni TFT LCD
- Video signal IO: VGA / DVI / HDMI
- High reliability for 24/7 operation
- Industrial grade black painted metal chassis
- Built-in speaker / Auto brightness control

SPECIFICATIONS:

Function	Items	Description	Remark	
Display	Display area (mm)	941.184 (H) x 529.416 (V)	42.5" 16:9 diagonal	
	Brightness (nits)	1000		
	Optimum resolution	1920 x 1080	Hi-Tni IPS cell	
	Contrast Ratio	1100:1		
	View angle (H/V)	178 /178 degree	All directions	
	Backlight Life	50,000 hours (typ.)		
System	Video input	VGA / DVI / HDMI		
	Video output	NA		
	Audio output	Built-in	Yes	
		Extend	(Option)	
	Memory	NA		
	Storage	NA		
	Ethernet	NA		
Wireless	NA			
Touch panel	Type	NA		
	Protection glass	NA		
	Support OS	NA		
Special Control	Manual	(Option)		
	OSD	5 keys at back side		
	RS232	Yes		
	Display feedback	NA		
Power	Power Input voltage	24V DC	Connector: GX16-2	
	Consumption(W)	150 (typ.)		
Mechanical	Outline (mm)	963.60 x 557.90 x 87.11 mm	Without brackets and handles	
	Mounting	400x400 (mm) VESA	(Option)	
	Others	NA		
Environment	Operating temp.	<u>0~45 0C</u>		
	Storage temperature	<u>-10~55 0C</u>		
	IP protection	NA		
	Anti-vandal	(TBD)		
	Auto brightness	Yes		
	Outdoor visibility enhance	(Option)		
	Direct sunlight	NA		
	Certification	CE / FCC		

