

IP-PoE Monitor (16CH)

10.1" 16CH-IP Monitor (LED Backlight) 16:10, 1280x800 350nit
800:1, RJ45x1(10/100M); Full HD*1; Mouse*1
Aluminum frame/ Metal case; Stand
(max. 16ch IP CAMERA support)



MODEL: HIPW1010-16PoE


FEATURES:

H.265	ONVIF	RTSP	Dual Stream Support	Mouse	GUI	SEQ	LED	Bracket
MAX. 16CH	PoE	24H	OSD	Speaker	Metal Case	PTZ Support	Record Support	VESA

OPTIONS:

No PoE	Color Option
Rack mount	AG Glass

DIAGRAM



INTERFACE

DC12V IN	ETHERNET	USB 1 IN	USB 2 IN	DVI-D IN	HDMI 1 IN	VGA IN	Audio L R	Earphone Out	eSATA Port
----------	----------	----------	----------	----------	-----------	--------	-----------	--------------	------------

SPECIFICATIONS:

LCD Panel	10.1"
Viewable area	216.96 x 135.6
Profile Ratio	16 : 10
Max. Resolution	1280 x 800
Display Colors	16.2M
Brightness	350 cd/m2
Contrast	800 : 1
Response Time	10 / 15 ms
View Angle	85/85/85/85
Full HD Input	1xHDMI (Type A)
Audio Input(R/L)	2xRCA
PC Input	1xVGA Input/1xDVI Input
Earphone Out	1xPhone Jack 3.5ψ
Speaker	2xBuilt-in Speaker (2w)
IP Video Support	16CH(2592x1944)/8CH(2592x1944)/4CH(2592x1944)
Network Port	1xRJ45,10/100M
USB Port	2xUSB 2.0 ports
PoE Power Source	PoE RJ45 Ethernet Cable
PoE Input DC Range	36VDC to 57 VDC(Complies with IEEE802.3at/4-Pairs) (Required PoE Device up to 40W)
Power Input(No PoE)	AC 100-240V 50/60Hz ,Adaptor DC 12V/5A
Power Consumption	Approx. 9 Watt
Housing	Metal Frame/ Casing
Dimension(mm)	255.1 x 173.6 x 59.1
Weight(kgs)	1.7 kgs
Operating Temperature	0~50 °C