



### LCD Screen

Manufacturer		
LCD Origin	South Korea	
LCD Type	Samsung grade A industrial TFT LCD Panel	
Display Size	17.0 inch diagonal (337.92H x 270.34V)	
Resolution	1,280 x 1,024, SXGA	
Display Color	16.2M color	
Brightness	300 cd/m <sup>2</sup>	
Contrast Ratio	500 : 1 (Typical)	
Pixel Pitch	0.264 x 0.264 mm	
Viewing Angle	75 / 75 / 75 / 60 (L / R / U / D)	
OSD Control	Brightness, Contrast, Phase & Clock, Color, H & V position, Auto-tune & Recall	
VGA Connector	D-Sub 15 pin VGA analog	
Video Input	S-Video and Composite ( Optional )	
LCD MTBF	50,000 hrs	
Mounting	Panel, wall-mount or VESA arm	
Dimension	414.8(W) x 328(H) x 57.3(D) mm	
Weight	5.5 kg (Net) / 7.5 kg (Gross)	
Packing	630(L) x 550(W) x 110(H) mm	

### Touch Screen

Type	Resistive	Surface Wave
Thickness	2mm	3mm
Light transmission	82%	90%
Controller Interface	Serial / USB	Serial / USB
Durability	35 Million	50 Million
OS Support	Windows XP, 2000, NT, 98, DOS and	

### External Power Adapter

AC Input	110V ~ 220V AC Input
DC Input	12V@5A Output
AC Cable Length	180cm
DC Cable Length	182cm
Adapter Size	108(L) x 64(W) x 30(H) mm

### Environmental

Operating Temperature	0 to 50°C
Storage Temperature	-25 to 60°C
Humidity	90%, non condensing
Shock	50G peak acceleration ( 11ms, since wave )
Vibration	10~300Hz/1.5G (10min/cycle)
Safety Approval	CE, FCC

### Ordering Information

Model	Description
iAP-1700	17" Aluminum Front panel
iAP1700-TRS	17" Al. FP w/ Res. touch screen (Serial)
iAP1700-TRB	17" Al. FP w/ Res. touch screen (USB)
iAP1700-TWS	17" Al. FP w/ Wave touch screen (Serial)
iAP1700-TWB	17" Al. FP w/ Wave touch screen (USB)
iAP-1700AV	17" Aluminum Front panel w/ Video Input
iAP1700AV-TRS	17" Al. FP w/ Video, & Res. touch screen (Serial)
iAP1700AV-TRB	17" Al. FP w/ Video, & Res. touch screen (USB)
iAP1700AV-TWS	17" Al. FP w/ Video, & Wave touch screen (Serial)
iAP1700AV-TWB	17" Al. FP w/ Video, & Wave touch screen (USB)