## Front IP65, NEMA 4 Rugged Protection Panel Mount



IP65-rated front bezel 8" 400nits SVGA TFT Fanless Touch Panel 10-points Multi Capacitive Touch Computer with N3350 (Apollo Lake), 8 GB DDR3L SO-DIMM, 120GB M.2 SSD, Win 10 IoT 2019 64-bit, 12V DC-input Support, with EOS, OVP design


# MODEL: JTCW0800AL

#### **FEATURES**


**EXTERNAL I/O** 

- 8.0" 400 nits high brightness TFT LCD with LED backlight
- 10-points Multi Capacitive Touch
- Enclosed in robust aluminum casings
- A true Flat, easy-to-clean front surface with edge-to-edge design
- USB3.0 Support Lock Device
- Front IP65 for protection against water and dust
- 12V DC-input Support, with EOS, OVP design





#### DRAWINGS



DRAWINGS FOR REFERENCE: This is subject to change without Notice. Final Drawings will be provided for Approval after Order.



### **SPECIFICATIONS:**

| Display   | Touch Screen  |
|---|---|
| IP65, NEMA 4 rugged protection, metal front bezel | Projected capacitive type   |
| 8.0" With LED Backlight                           | 163.05 x 122.54mm ±0.2mm active range                               |
| 400 nits  | Transparency $\geq 85\%$  |
| 16.7M display color                               | Operating force ≤ 50g   |
| 1024 x 768 @60Hz resolution                       | Surface Hardness ≧ 6H (JIS-5400)                                    |
| 160°/160° viewing angle (H/V)                     | Glass haze value ≦ 3%   |
| 0.158 x 0.158mm pixel pitch                       | Main System   |
| 4:3 aspect ratio                                  |   |
| 700:1 contrast ratio                              | Intel® Apollo Lake N3350 1.1GHz/DC processor                        |
| 30ms response time                                | 1* DDR3L SO-DIMM (Max 8GB)  |
| Case  | 128MB SPI Flash ROM   |
| Aluminum panel                                    | Watchdog Timer 256 levels, 0~255 sec.                               |
| Iron case   | OS Support Windows 10 / Linux                                       |
| Silver + white color                              | Expansion   |
| Spray paint coating requirement                   | 1* Mini PCIe for WIFI or 3G/4G                                      |
| Storage   | Power Input   |
| 120GB M.2 SSD                                     | AC version: 100~240V AC-DC 60W power adapter or                     |
|   | DC version: 12VDC with over current protection fuse                 |
| I/O Connector<br>2* USB3.0                        | Dimensions  |
| 1* RS232/422/485 + 1* RS232                       | 199.05 * 158.54 * 57.70mm   |
| 1* HDMI   | Safety  |
| 1* Realtek® RTL8111H GbE                          | Shock: 11ms duration  |
| 1* Locking Jack 12V DC input                      | Vibration: 5~500Hz/1 Grms   |
| 1* SIM card slot                                  | Warranty  |
| 1* Power button                                   | 2 Years Limited Warranty (Panel and Touch are only 1 Year Warranty) |
| Power Consumption                                 |   |
| 13W   |   |
| Compliance  |   |
| CE, FCC, IP65(Front)-Option                       |   |
| Temperature                                       |   |
| Operating: -10°C ~ 60°C                           |   |
| Storage:  |   |

\*Specifications subject to change without notice, not responsible for typographical errors.

#### **ACCESSORIES:**

Power cord Adapter 12V/5A 60W L-Antenna

