

True Flat Bezel Panel PC Touchscreen

15.0" 350nits Panel PC IP65, NEMA 4 rugged protection, metal front bezel, 5 Wire Resistive Touch/Anti-Reflection Protection Glass. Intel Bay Trail-D J1900 2.0GHz/QC CPU 4GB Memory,

MODEL: JTPC1500R-J




FEATURES:

- 15.0" 350 nits high brightness TFT LCD with LED backlight
- 5 Wire Resistive Touch/Anti-Reflection Protection Glass
- Cable less, Streamlined enclosure for highly efficient heat dissipation Enclosed in robust aluminum casings
- Strong solid aluminum frame design and Fanless cooling system
- Support Open frameless design
- Design for easy Wall mount, Panel Mount, VESA Mount installation
- A true Flat, easy-to-clean front surface with edge-to-edge design
- USB3.0 Support Lock Device
- IO Ports designed for easy connection
- 9-28V DC-input Support, with EOS, OVP design



EXTERNAL I/O



SPECIFICATIONS:

Display	
Front Bezel	- NEMA 4 rugged protection, metal front bezel
Display Type	- 15.0" With LED Backlight
Brightness (cd/m ²)	- 350 nits
Display Color	- 262K
Resolution	- 1024 x 768 @ 60Hz
Viewing Angle (H/V)	- 170°/160°
Pixel Pitch	- 0.297 x 0.297mm
Aspect Ratio	- 4:3
Contrast Ratio	- 700:1
Response Time	- 5.7 ms
Touch screen	
Type	- 5 wires analog resistive type
Active Range	- 304.10 x 228.10mm ±0.2mm
Operating Force	- ≤ 80g
Transparency	- 80 ±3%
Surface Hardness	- ≥ 3H (ASTM D3363, pressure 750g/45°)
Knock test	- 10,000,000 times keystrokes
CASE	
Panel Material	- Aluminum
Case Material	- Iron
Color	- Silver + white
Coating Requirement	- Spray Paint
Main System	
CPU	- Intel® Bay Trail-D J1900 2.0GHz/QC
RAM	- 4G 1333MHz DDR3L SAMSUNG DRAM
BIOS	- 64MB SPI Flash ROM
Storage	- 1* 2.5" SATA HDD - 1* M.2 connector (2242/2260/2280)
Watchdog Timer	- 256 levels, 0~255 sec.
OS Support	- Windows 7 / 8.1 / 10 / Linux(Optional)
I/O Connector	
I/O Ports and Switches	- 2* USB3.0 - 4* USB2.0 - 2* RS232/422/485 - 2* RS232 - 1* CRT - 1* 8bit GPIO - 2* LAN (Intel® I211AT Gigabit LAN) - 1* Locking Jack 9~28V DC input - 1* Power button

SPECIFICATIONS:

Expansion Interface	
Expansion	- 1 * PCI-E mini card for WIFI or 3G/4G - 1 * SIM card holder for 3G/4G
Power	
Power Input	- AC version: 100~240V AC-DC 60W power adapter or - DC version: 9-28VDC with over current protection fuse
Power Consumption	- 35W
Dimensions	
Case Dimensions	- 366.0*290.0*74.0mm
Packing Dimensions	- Net Weight: KG - Gross Weight: KG - Color Box dimension: (W) * (D) * (H)mm
Certifications	
Certifications	- CE, FCC, IP65(Front)
Environment	
Temperature	- Operating: -0°C ~ 60°C (with W.T. DRAM/HDD in airflow condition) - Operating: -0°C ~ 60°C (with W.T. DRAM/HDD) - Storage: -20°C ~ 85°C
Shock	- Operating: 15G, 11ms duration
Vibration	- Operating: 5~500Hz/1 Grms
Warranty	
Warranty	- 2 Years Limited Warranty (Panel is only Warranty 1Year)

MECHANICAL DRAWINGS:

