

Multi Touch - MEDIA PLAYER

Media player 10.1"1280*800+ multi touch+RK3288 8 cores
Cortex A17 1.8Ghz CPU+ Android 5.1 OS+2G RAM/4G
eMMC+POE function

Model: KAOW1010



FEATURES

- 10.1" diagonal, IPS, 16:10, 1280x800 Resolution, Viewing angles: 85/85/85/85, Contrast ratio: 800:1
- 10 point capacitive touch panel (optional)
- Optional Power over Ethernet (PoE+)
- Mechanical drawings available upon request
- Highly reliable media handling platform
- S/PDIF digital audio
- Engaging interactive controls via GPIO and UDP
- 1x USB 2.0
- Serial and IR control for expanded interactive options
- WiFi / Bluetooth Module (optional) MBS-WIFI1-OPT - enables KAOW1010 with BrightSign Built-In to network using Wi-Fi and operate BrightBeacon via Bluetooth
- BrightSign approved MicroSD memory cards are used to deliver reliable and quality performance for all Mimo Vue with BrightSign Built-In
- Powerful video engine (HS124 supports Full HD 1080p60 single decode; HS144 supports 4Kp60 single decode)
- Low-power, fan-less design
- HDMI output (HS124 supports 1.4; HS144 supports 2.0a) with CEC
- Mainstream HTML5 Engine
- Highly reliable media handling platform
- 100baseT Ethernet • S/PDIF digital audio
- Engaging interactive controls: GPIO, UDP, 1x USB 2.0, Serial and IR controls
- Wi-Fi / Bluetooth module (optional)
- SD Card, 8/16/32GB for KAOW1010 with BrightSign Built-In (MBS-SD08-OPT / MBS-SD16-OPT / MBS-SD32-OPT)

APPLICATIONS

- Kiosk information system
- Gaming and amusement
- POP/POS
- Conference Room Scheduling
- Elevator / In-Wall Digital Signage
- Interactive Consumer Engagement



SPECIFICATIONS

- 10.1" diagonal, IPS,
- 16:10 Aspect Ratio
- 1280x800 Resolution
- Multi Point Capacitive Touch (optional)
- Viewing angles: 85/85/85/85
- Contrast ratio: 800:1
- Luminance, White: 350 CD/m2
- HD class performance; runs BrightSign software or compatible CMS partners software
- H.265/H.264 video decode
- Video output up to 1080p60
- 10-bit video output (using H.265)
- Hardware accelerated HTML5 support
- Operating Temperature -10 to 50c
- VESA75 mounting for secure installation
- Power over Ethernet (POE -- Optional)
- Applications include:
 - Retail POS environments
 - Interactive Information Kiosks for Retail, Museums and Entertainment
 - Signage for Corporate Conference Rooms, Schools, and Hospitality
 - Medical Signage for Hospitals and Offices



BrightSign FEATURES

