

KCH Series

FULL IP65 TOUCH LCD MONITOR

A full range of solutions for a wide variety of industrial criteria including extreme temperature resistance or sunlight readable



Model: KCH1500SIP-FTR

15" True Flat Touch Industrial Display-Fully Enclosed NEMA 4/IP65, Resolution:1024x768, 400nits with 5 wires resistive touch solution



Touch Function



IP65 chassis, IP65 connectors, IP65 power adapter (alternative)



Waterproof Design

Stainless steel



Housing Design



OSD Controller

Rear side

Features:

- Fanless design and compact solution
- Fully IP65 compliant 6-sided stainless steel chassis
- Resolution 1024 x 768dpi
- PCAP / 5 wires resistive touch solution
- All IP65 waterproof connectors
- 1 X VGA; 1 x USB or RS232
- VESA mounting



Waterproof



Anti-oil



Dustproof



Corrosion-proof

Specifications:

I/O Port		VGA			
		USB or RS232			
Power		DC IN 12 V(Default) or DC IN 19~36V			
Touchscreen		OS Support			
PCAP/5 wire resistive		Win 7,8,10; Win Embedded 7,8,10, Win pro 7,8,10			
Display					
Size	15" TFT (4:3)				
Resolution	1024 x 768				
Colors	16.2M				
Luminance (cd/m2)	400				
Contrast Ratio	700:1				
View Angle (H/V)	160/160				
Mechanical & Environmental					
Operation Temperature	0 ~ 45°C for PCAP; -20~55°C for RW				
Storage Temperature	-10°C ~ 70°C				
Storage Humidity	10 ~ 90%, non-condensing				
Mount	VESA mounting(100X100mm)				
Dimension (W x H x D mm)&Weight	438.2 x 335 x 63(9kg)				
Optional					
DVI	1				
HDMI	1				
No Touch Screen	1				
AR Glass	1				
Optional High Brightness Panel					
Resolution	1024x768				
Color	16.2M	16.7M	16.7M	16.2M	16.7M
Luminance(cd/m2)	2000	1600	1000	1000	800
Contrast Ratio	700:1	700:1	1700:1	700:1	700:1
Viewing Angle (H/V°)	160/160	160/160	170/170	160/160	160/160

