


Aluminum True Flat Front Touch Panel PC

15" Aluminum Front Bezel True Flat Touch Panel PC, True flat PCT touch screen , i7 4650U , 2 x HDMI , 2 x RS232 , 4 x USB , 2 x LAN , 1 x 24V DC in , VESA mounting & panel mount , resolution : 1024 x 768 dpi

Model: KPC1500-i7-FPCAP



FEATURES:

- Fanless design and compact solution
- 4th Gen Intel i7 4650U CPU
- Resolution 1024 x 768 dpi
- 5 wire Resistive / PCAP touch solution
- IP65 Silver aluminum front bezel
- Various Sunlight Readable High Brightness Panel for choose
- 4 x USB, 2 x HDMI, 2 x LAN, 1 x RS232
- Panel mount & VESA mounting & Clips

SPECIFICATIONS:

System	
CPU	4th Gen Intel Core i7 4650U CPU (On Board)
Memory	2 x 204-pin DDR3L SODIMM up to 16GB
H/W Monitor	
Watchdog Timer	Watch Dog Timer 256 Level
I/O Ports	
RS232	1
GLAN	2
USB	2x USB 2.0; 2 x USB3.0
HDMI	1
Line-Out/In Mic in	1
Storage	
Storage	1 x SATA 2.0 2.5" HDD/SSD
Expansion	
Mini-PCle	1 x Full-size (one w/ mSATA)
Power Requirement	
Power Input Voltage	DC in 12V or 19~24V
Touch Screen	
Touch screen	PCAP touch solution
OS support	
Win Pro 7,8,10 ; Embedded Win 7, 8,10	

Display	
Size	15" TFT (4:3)
Resolution	1024 x 768
Colors	16.2M
Luminance (cd/m2)	400
Contrast Ratio	700:1
View Angle (H / V)	160/160
Mechanical & Environmental	
Operation Temp	0 ~ 45°C
Storage Humidity	10 ~ 90%, non-condensing
Mount	Clip mount, Panel mount & VESA mounting(100X100mm)
Dimension (W x H x D mm) & Weight	441 x 322 x 68.6mm (11kg)
Optional	
RS232/422/485	2
External antenna	1 or 2
Waterproof Sponge	1
Front IP66 Bezel with Oring	1
Clip	8
No Touch Screen	1

Optional High Brightness Panel					
Resolution	1024 x 768				
Color	16.2M	16.7M	16.7M	16.2M	16.2M
Luminance(cd/m2)	2000	1600	1000	1000	800
Contrast Ratio	700 : 1	700:1	1700:1	700:1	700:1
Viewing Angle (H/V°)	160/160	160/160	170/170	160/160	160/160

MECHANICAL DRAWINGS:

15 " PANEL CUT - OUT Dimensions : 358.00 x 289.30 m/m

