

Aluminum True Flat Front Touch Panel PC

15.6" Aluminum Front Bezel True Flat Touch Panel PC, True flat PCT touch screen , i3 4010U , 2 x HDMI , 2 x RS232 , 4 x USB, 2x LAN, 1 x DC in 24V, VESA mounting & panel mount , resolution : 1920 x 1080 dpi



Model: KPCW1560HD-i3-FPCAP

FEATURES:

- Fanless design and compact solution
- 4th Gen Intel i3 4010U CPU
- Resolution 1024 x 768 dpi
- 5 wires resistive / PCAP touch solution
- IP65 Silver aluminum front bezel
- Various Sunlight Readable High Brightness Panel for choose
- 4 x USB, 2 x HDMI, 2 x LAN, 1 x RS232
- Panel mount & VESA mounting & Clips

SPECIFICATIONS:

| System | |
|---------------------------------------|--|
| CPU | 4th Gen Intel Core HSW ULT i3 4010U CPU (On Board) |
| Memory | 2 x 204-pin DDR3L SODIMM up to 16GB |
| H/W Monitor | |
| Watchdog Timer | Watch Dog Timer 256 Level |
| I/O Ports | |
| RS232 | 1 |
| GLAN | 2 |
| USB | 2x USB 2.0; 2 x USB3.0 |
| HDMI | 1 |
| Line-Out / Mic In | 1 |
| Storage | |
| Storage | 1 x SATA 2.0 2.5" HDD/SSD |
| Expansion | |
| Mini-PCIe | 1 x Full-size (one w/ mSATA) |
| Power Requirement | |
| Power Input Voltage | DC in 12V or 19~24V |
| Touch Screen | |
| Touch screen | PCAP |
| OS support | |
| Win Pro 7,8,10 ; Embedded Win 7, 8,10 | |

| Display | |
|-----------------------------------|--|
| Size | 15.6" TFT (16:9) |
| Resolution | 1920 x 1080 |
| Colors | 16.2M |
| Luminance (cd/m2) | 400 |
| Contrast Ratio | 500:1 |
| View Angle (H / V) | 140/120 |
| Mechanical & Environmental | |
| Operation Temp | 0 ~ 45°C |
| Storage Humidity | 10 ~ 90%, non-condensing |
| Mount | Clip mount, Panel mount & VESA mounting(100X100mm) |
| Dimension (W x H x D mm) & Weight | 463x298.6x71 (14kg) |
| Optional | |
| RS232/422/485 | 2 |
| External antenna | 1 or 2 |
| Waterproof Sponge | 1 |
| IP66 front Bezel with Oring | 1 |
| Clip | 10 |
| No Touch Screen | 1 |

MECHANICAL DRAWINGS:

