

Stainless Steel True Flat IP65 Touch Panel PC

Fanless 15" Fully IP65 stainless steel panel PC
 with true flat PCT T/S, i7 6600U, 2 x USB, 2 x RS232, 2 x GLAN, 1 x 12V
 DC in PW, external heatsink, VESA 100 x 100 & Yoke mount, Res : 1024 x
 768 dpi



Model: KSP1500-i7-FPCAP

FEATURES:

- Fanless design and compact solution
- 6th Gen Intel Core i7 CPU
- Resolution 1024 x 768 dpi
- True Flat 5W / PCAP touch solution
- Fully IP65 compliant 6-sided stainless steel chassis
- All IP65 stainless connectors
- 2 x USB, 2 x RS232, 2 x GLAN
- VESA mounting

SPECIFICATIONS:

System	
CPU	6th Gen Intel Core i7 -6600U
Memory	2 x 204-pin DDR3L SODIMM up to 16GB
H/W Monitor	
Watchdog Timer	Watch Dog Timer 256 Level
I/O Ports	
RS232	2
GLAN	2
USB	2
Storage	
Storage	1 x SATA 2.0 2.5" HDD/SSD
Power Requirement	
Power Input Voltage	DC in 12V
Touch Screen	
Touch screen	PCAP
OS support	
Win Pro 7,8,10 ; Embedded Win 7, 8,10	

Display	
Size	15" TFT (4:3)
Resolution	1024 x768
Colors	16.2M
Luminance (cd/m2)	500
Contrast Ratio	700:1
View Angle (H / V)	160/160
Mechanical & Environmental	
Operation Temp	0 ~ 45°C
Storage Humidity	10 ~ 90%, non-condensing
Mount	VESA mounting(100 x 100mm)
Dimension (W x H x D mm) &Weight	438.2 x 335 x 63 (9kg)
Optional	
RS232 /422/485	1
External antenna	1 or 2
Full IP65 Power adaptor	1
No Touch Screen	1
Optical Bonding	1
AR Glass	1

Optional High Brightness Panel					
Resolution	1024 x 768	1024 x 768	1024 x 768	1024 x 768	1024 x 768
Color	16.2 M	16.7M	16.7M	16.2M	16.7M
Luminance(cd/m2)	2000	1600	1000	1000	800
Contrast Ratio	700 : 1	700:1	1700:1	700:1	700:1
Viewing Angle (H/V°)	160/160	160/160	170/170	160/160	160/160



MECHANICAL DRAWINGS:

