

Stainless Steel True Flat IP65 Touch Panel PC

Fanless 19" Fully IP65 stainless steel panel PC
 with true flat PCT Res T/S, J1900 , 2 x USB , 2 x RS232 2 x GLAN , 1 x 24V
 DC in PW, VESA 100 x 100 & Yoke mount Re 1280 x 1024 dpi



Model: KSP1900-J-FPCAP-24

FEATURES:

- Fanless design and compact solution
- Intel Bay Trail Quad Core J1900 2.0GHz CPU
- Resolution 1280 x 1024 dpi
- True Flat 5W / PCAP touch solution
- Fully IP65 compliant 6-sided stainless steel chassis
- All IP65 stainless connectors
- 3 x USB, 2 x RS232, 1 x GLAN
- VESA mounting

SPECIFICATIONS:

System	
CPU	Intel Bay Trail D-J1900 2.0GHz Quad Core Processor (On Board)
Memory	1 x 204-pin DDR3L SODIMM up to 8GB
H/W Monitor	
Watchdog Timer	256-Level Watchdog Timer
I/O Ports	
RS232	2
GLAN	2
USB	3
Storage	
Storage	1 x SATA 2.0 2.5" HDD/SSD
Power Requirement	
Power Input Voltage	DC in 24V
Touch Screen	
Touch screen	PCAP
OS support	
Win Pro 7,8,10 ; Embedded Win 7, 8,10	

Display	
Size	19" TFT (4:3)
Resolution	1280 x 1024
Colors	16.7 M
Luminance (cd/m2)	250
Contrast Ratio	1000:1
View Angle (H / V)	170/160
Mechanical & Environmental	
Operation Temp	0 ~ 45°C
Storage Humidity	10 ~ 90%, non-condensing
Mount	VESA mounting(100 x 100mm)
Dimension (W x H x D mm) & Weight	521.4 x 434.3 x 67.1 (12kg)
Optional	
RS232 /422/485	1
Second Lan	1
Full IP65 Power adaptor	1
No Touch Screen	1
AR Glass	1
Optical Bonding	1

Optional High Brightness Panel				
Resolution	1280 x 1024	1280 x 1024	1280 x 1024	1280 x 1024
Color	16.7M	16.7M	16.7M	16.7M
Luminance(cd/m2)	1600	1000	1000	800
Contrast Ratio	1000:1	2000:1	1000:1	1000:1
Viewing Angle (H/V°)	170/160	178/178	160/170	170/160



MECHANICAL DRAWINGS:

