

Stainless Steel True Flat IP65 Touch Panel PC

Fanless 21.5" Fully IP65 stainless steel panel PC
 with true flat PCT T/S, i3 7100U , 2 x USB , 2 x RS232 2 x GLAN , 1 x 12V
 DC in PW, external heatsink, VESA 100 x 100 & Yoke mount, Res : 1920 x
 1080 dpi



Model: KSPW2150-i3A-FPCAP

FEATURES:

- Fanless design and compact solution
- Intel Core i3 CPU
- Resolution 1920 x 1080 dpi
- PCAP touch solution
- Fully IP65 compliant 6-sided stainless steel chassis
- All IP65 stainless connectors
- 2 x USB, 2 x RS232, 2 x GLAN
- VESA mounting
- 316 for stainless steel Enclosure optional

SPECIFICATIONS:

| System | |
|---------------------------------------|--|
| CPU | 7th Gen Intel Core i3 7100U CPU |
| Memory | 2 x 204-pin DDR3L SODIMM up to 16GB |
| H/W Monitor | |
| Watchdog Timer | 256-Level Watchdog Timer |
| I/O Ports | |
| RS232 | 2 |
| GLAN | 2 |
| USB | 2 |
| Storage | |
| Storage | 1 x SATA 2.0 2.5" HDD/SSD |
| Power Requirement | |
| Power Input Voltage | DC in 12V |
| Touch Screen | |
| Touch screen | PCAP |
| OS support | |
| Win Pro 7,8,10 ; Embedded Win 7, 8,10 | |

| Display | |
|-------------------------------------|----------------------------|
| Size | 21.5" TFT (16:9) |
| Resolution | 1920 x 1080 |
| Colors | 16.7 M |
| Luminance (cd/m2) | 300 |
| Contrast Ratio | 3000:1 |
| View Angle (H / V) | 178/178 |
| Mechanical & Environmental | |
| External Heat sink | 1 |
| Operation Temp | 0 ~ 45°C |
| Storage Humidity | 10 ~ 90%, non-condensing |
| Mount | VESA mounting(100 x 100mm) |
| Dimension (W x H x D mm) &Weight | 607 x 401 x67.1 (13kg) |
| Optional | |
| RS232 /422/485 | Back Side |
| External antenna | 1 or 2 |
| Full IP65 Power Adaptor | 1 |
| No Touch Screen | 1 |
| AR Glass | 1 |

| Optional High Brightness Panel | |
|--------------------------------|-------------|
| Resolution | 1920 x 1080 |
| Color | 16.7M |
| Luminance(cd/m2) | 1600 |
| Contrast Ratio | 900:1 |
| Viewing Angle (H/V°) | 178/178 |



MECHANICAL DRAWINGS:

