



# High Brightness (1500 nits)

Model: LCHH1001

## Sunlight Readable 10.4" Chassis mount monitor

10.4" TFT LCD panel, built-in 1500 nits high bright for sunlight readable LCD display, High transmittance color filter, High transmission polarizing plates, Low Power Consumption, Suitable for kiosk, advertising, POS, marine, transportation, LCD TV, Gaming, studio display, gas pump....

### Key Features:(For POS, ATM and Industrial Application)

- Very High Brightness
- Wide Viewing Angle
- High Contrast Ratio
- Short Response Time
- Long Lamp Life
- Thin and Light
- LVDS



LCHH1001	
LCD Display	10.4" TFT Active Matrix Panel
Brightness	1500 cd/m <sup>2</sup> (6 CCFL)
Pixel Pitch(mm)	0.264(H) x 0.264(V)
Max. Resolution	800x 600 (SVGA)
Contrast Ratio	500 : 1
Display Area	211.2 x 158.4mm
Response Time(Typ.)	35ms(Typ.)
Display Colors	262,144 colors
Viewing Angle	+60°~-60°(H), +40°~-60°(V)
Video	RGB Analog 0.7V Peak to Peak
Sync	LVDS
Signal Connector	15 Pin mimi D-sub
F/ R Control Button	Power Switch, Menu,Select (+,-), Auto
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock, Management
S-video / AV connector	Optional
Anti-glare Glass	Coting
Power Consumption	30W
Dimensions (mm)	340 x 228 x 54.2mm
Weight (Net)	3.15kg