



High Brightness (700 nits)

Model: LCHH1900W

Sunlight Readable **19"** Chassis mount LCD monitor

19" TFT LCD panel, Built-in 700 nits high bright for sunlight readable LCD display, High transmittance color filter, High transmission polarizing plates, Low Power Consumption, Suitable for kiosk, advertising, POS, marine, transportation, LCD TV, gaming, studio display, gas pump....

- MVA technology, no viewing limit
- High contrast: 800:1
- High resolution:1280x1024 SXGA
- Low power consumption: 80w
- High brightness: 700 nits
- Input: VGA
- Narrow boarder design
- Pivot stand
- **Application: medical**



LD1946 (AU M190EG01)

LCD Display	19" TFT Active Matrix Panel
Brightness	700 cd/m ²
Pixel Pitch(mm)	0.294(H) x 0.294(V)
Max. Resolution	1280 x 1024 (SXGA)
Contrast Ratio	800 : 1
Display Area	376.32 x 301.056mm
Response Time(Typ.)	20ms(Typ.)
Display Colors	16.7M
Viewing Angle	+85°~-85°(H), +85°~-85°(V)
Signal Connector	15 Pin D-sub, 29 Pin DVI
Video	RGB Analog 0.7V Peak to Peak
Sync	LVDS
F/ R Control Button	Power Switch, Menu, Select (+,-), Auto
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock, Management
Video input option	S-video, DVI input
Power Consumption	80W
Dimensions (mm)	418.3 x 343.05 x 52.9 mm
Weight	7kg