

2U 4" x 4 Rack Mount Video Serial monitor



Model: LMR2440



Features

- 4 X 4" LCD Screens
- 2 Video BNC Inputs
- 1 Video BNC Output
- Individual brightness / contrast control for each screen
- Tilt adjustment for optimum viewing angle
- Heavy duty metal housing
- Universal power supply

Specification

DISPLAY SCREEN

SIZE: 4 INCHES (10 cm)
ACTIVE AREA: 82.08(W) x 61.56(H)
ELEMENT: COLOR TFT LCD
RESOLUTION: 960(W)X240(H)

VIDEO SYSTEM: NTSC / PAL Dual System

NTSC	PAL
fH : 15.75 Khz	fH : 15.625 Khz
fV : 60 Hz	fV : 50 Hz
f_c : 3.58 MHz	f_c : 4.43 MHz

POWER SOURCE

DC 12V

RANGE OF OPERATING VOLTAGE

DC 9 ~ DC 13V

VIEWING ANGLE

L/R:75° Top:60° Down:70°

CONTRAST RATIO

250 : 1

BRIGHTNESS

290 cd/m²

POWER CONSUMPTION

135 mA , 1.62 Max.

OPERATING TEMPERATURE

0°C ~ 60°C

STORAGE TEMPERATURE

-20°C ~ 70°C

RELATIVE HUMIDITY

5-95% RH

OVERALL DIM.

489.0(W) x 87.88(H) X 61.0 (D)

WEIGHT

3.2 kg



i-Tech Company LLC

TOLL FREE: (888) 483-2418 • EMAIL: info@iTechLCD.com • WEB: www.iTechLCD.com

2U 4" x 4 Rack Mount Video Serial monitor

Mechanical Drawing

