

HOTEL SELF CHECK-IN Kiosk

11.6" LCD Help Desk Kiosk w/ N3350 2.24 Ghz CPU,
1366x768, 220nits Viewing Angle 85/85/85/85 and
PCAP Touch

Model: MPK1160PT

Self-Check-In touchscreen kiosk that delivers on guest expectations nowadays with no more lines. Self-Service Kiosk at hotel lobby have exploded in recent years. These unique kiosk design can streamlining the check in and out process while freeing up staff to other service areas.

FEATURES:

- Highly secure metal enclosure
- Heavy duty design for public use
- Compact design

EXPERIENCE:

- Hotel Check-in Guide
- Bank Open Account Guide
- Questionnaire Guide



SPECIFICATIONS:

Processor System	CPU (On Board)	N3350
	FCBGA1170	
	Frequency	Base Frequency 1.04 GHz , Burst Frequency 2.24 GHz
	Cache	2 MB
	Main Board	MS-9818
	System Chipset	Intel® Braswell
	BIOS	AMI 32-Mbit SPI Flash BIOS
Memory	Technology	DDR3L 1600 MHz
	Max. Capacity	8 GB
	Socket	1 x 204-pin SO DIMM
Display	Panel Size	11.6"
	Resolution	1366 x 768
	Viewing Angle	Horizontal : 85 / Vertical : 85 degree
	Brightness	220 cd/m2
	Color Support	262K Color
	Contrast Ratio	800
	Response Time	27 ms
Touchscreen	Touchscreen Type	Projected Capacitive (PCAP)
	Surface Hardness	6H
	Transparency	0.87
I/O Interface	USB	USB 3.0 x 4
	Serial Port	COM 1 : RS-232/422/485 ; COM2~4 : RS-232
Ethernet	Speed	10/100/1000 Mbps
	Controller	Realtek RTL8111G GbE LAN
	Connector	RJ45 x 2
Audio	Chipset	Realtek ALC887-VD2-CG HD Audio Codec
	Speaker	Internal : Speaker 8Ω/10W x2
Storage	HDD or SSD	Supports one 2.5" SATA HDD
Scanner	Passport/ID	CMOS 3.0 Megapixel (2048*1536), 400 dpi
Camera	ID Camera	500M pixels
Scanner	Honeywell or equivalent	CCD-2D
		CMOS sensor with 640 x 480 pixel resolution
RFID	13.56M Hz Mifare ISO14443A Standard	
	Read only	
Power	Power Type	Adapter 250W/24V
	Power Input	AC 100~240V @50~60Hz
	Battery	Lithium 3 V / 220 mA