

PAYMENT Kiosk

22" LCD Self Service / Payment Kiosk w/ ARM Cortex or N3350, 1920x1080, 250nits, Viewing Angle 89/89/89/89 and PCAP Touch

Model: MPK2200PT

Self-Check-In touchscreen kiosk that delivers on guest expectations nowadays with no more lines. Self-Service Kiosk at hotel lobby have exploded in recent years. These unique kiosk design can streamlining the check in and out process while freeing up staff to other service areas.

FEATURES:

- Slim profile for space-constricted environments
- Heavy duty design for continuous use in unsupervised area
- Modular design reduce total cost of ownership

EXPERIENCE:

- Hotel Self Check-in



SPECIFICATIONS:

		Android Base	Window Base
Processor System	CPU	ARM Cortex-A9 4 cores Processor	N3350
	Frequency	1.1 GHz	Base Frequency 1.04 GHz , Burst Frequency 2.24 GHz
	Cache	512 KB	2 MB
	Main Board	AR 100	MS-9818
Memory	Technology	DDR3 1066 MHz	DDR3L 1600 MHz
	Max. Capacity	1 GB	8 GB
	Socket	On Board	1 x 204-pin SO DIMM
Display	Panel Size	21.5"	
	Resolution	1920x1080	
	Viewing Angle	Horizontal : 89 / Vertical : 89 degree	
	Brightness	250 cd/m2	
	Color Support	16.7M	
	Contrast Ratio	3000	
	Response Time	25 ms	
Touchscreen	Touchscreen Type	Projected Capacitive (PCAP)	
	Surface Hardness	≥6H	
	Transparency	0.85	
I/O Interface	USB	USB 2.0 x 1	
Ethernet	Speed	10/100 Mbps	10/100/1000 Mbps
	Controller	SMSC LAN8720	Realtek RTL8111G GbE LAN
	Connector	RJ45 x 1	RJ45 x 2
Audio	Chipset	Realtek ALC5616,Ultra-Low Power Audio CODEC for Mobile Devices	Realtek ALC887-VD2-CG HD Audio Codec
	Speaker	Internal : Speaker 8Ω/2W x2	Internal : Speaker 8Ω/2W x2
Storage	NAND Flash	4GB	Supports one 2.5" SATA HDD
	SD Card	Support SD3.0	
Printer	2" (58mm) / 3" (80mm)		
	Auto Loading function		
	Paper near-end detection		
Credit Payment	Customized payment terminal holder		
Wifi (Optional)	802.11n 1T1R Solution for 2.4G Hz band		
Scanner	Honeywell or equivalent	CCD-2D	
		CMOS sensor with 640 x 480 pixel resolution	
RFID	13.56M Hz Mifare ISO14443A Standard		
	Transponder : read only		
Power	Power Type	Adapter 120W/24V	
	Power Input	AC 100~240V @50~60Hz	
	Battery	Lithium 3 V / 220 mAH	