

Model: MRKW2150PC-AO

FEATURES:

- Slim profile for space-constricted environments
- Various peripheral options for multi-application deployment
- Heavy duty design for continuous use in unsupervised area
- Modular design reduce total cost of ownership

EXPERIENCE

- Information Kiosk in Mall / Department Store / Hospital
- Price Check / Membership in Supermarket / Discount Store
- Ticketing Kiosk in Movie Theater / Golf Club
- Queuing Kiosk in Bank/ Hospital

SPECIFICATIONS:

Processor System	CPU	ARM Cortex-A9 4 cores Processor
	Frequency	1.1 GHz
	Cache	512 KB
	Main Board	AR 100
Memory	Technology	DDR3 1066 MHz
	Max. Capacity	1 GB
	Socket	On Board
Internal Display 21.5" (LED Backlight)	Panel Size	21.5"
	Resolution	1920x1080
	Viewing Angle	Horizontal: 89 / Vertical: 89 degree
	Brightness	250 cd/m2
	Color Support	16.7M
	Contrast Ratio	3000
	Response Time	25 ms
21.5" Touchscreen	Touchscreen Type	Projected Capacitive (PCAP)
	Surface Hardness	≧6H
	Transparency	85%
I/O Interface	USB	USB 2.0 x 1
Ethernet	Speed	10/100 Mbps
	Controller	SMSC LAN8720
	Connector	RJ45 x 1
Audio	Chipset	Realtek ALC5616,Ultra-Low Power Audio CODEC for Mobile Devices
	Speaker	Internal : Speaker 8f/2W x2

Cl	NAND Flash	4GB
Storage	SD Card	Support SD3.0
	NP-K3052D	3" (80mm)
Printer		Auto Loading function
		Paper near-end detection
Wifi (Optional)	RTL8811AU	802.11n 1T1R Solution for 2.4G Hz band
Coorne	Honeywell	CCD-2D
Scanner	N3680	CMOS sensor with 640 x 480 pixel resolution
חבות	RF 320	13.56M Hz Mifare ISO14443A Standard
RFID		Transponder: read only
	Power Type	Adapter 120W/24V
Power	Power Input	AC 100~240V @50~60Hz

OPTIONS:



Wifi




RFID/ Mifare






2"/3"/4" Thermal Printer

MECHANICAL DRAWINGS:







i-TECH
COMPANY
i-Tech Company LLC
TOLL FREE: (888) 483-2418 • EMAIL: info@iTechLCD.com
• WEB: www.iTechLCD.com