



1U 19" Widescreen LCD Drawer



NPW119


Drawer Features & Display Benefits

- 1U 19" widescreen LCD drawer with DVI-D/VGA input
- Short depth design of 460mm (18.1")
- Green LED-backlit panel technology
- Sliding LCD allowing LCD to remain open when the rack door is closed
- Enhanced aesthetics with molded front panel and two point lock



Options

- 3G/HD/SD-SDI Broadcast-grade input
- S-Video + Composite (BNC)
- HDMI or Audio input
- 48V, 24V or 12VDC power



Basic I/O: VGA and DVI-D

Options: HDMI, Audio, S-Video + BNC
SDI

** For the above options, casing depth will be extended from 460mm (18.1") to 530mm (20.9")

| LCD Panel | |
|----------------------|-------------------------------------|
| Manufacturer | Samsung |
| Diagonal size | 19" widescreen TFT |
| Max. Resolution | 1440 x 900 |
| Brightness (cd/m2) | 250 |
| Backlight | LED |
| Colors | 16.7 M |
| Contrast Ratio (typ) | 1000 : 1 |
| Viewing Angle (H/V) | 160° x 160° |
| Active area (mm) | 408 x 255 |
| MTBF (hrs) | 30,000 |
| Signal input | VGA or DVI-D |
| Casing Color | Black (RAL 9005) |
| Weight | |
| Net | 13 kgs (28.6 lbs) |
| Gross | 17 kgs (37.4 lbs) |
| Environmental | |
| Operating | 0 to 50°C Degree |
| Storage | -5 to 60°C Degree |
| Relative humidity | 5-90%, non-condensing |
| Shock | 10G acceleration (11 ms duration) |
| Vibration | 5~500Hz 1G RMS random vibration |

| | |
|-------------|---|
| Regulatory | FCC, CE, RoHS |
| Power | |
| Input | Auto-sensing 100 to 240VAC, 50 / 60Hz |
| Consumption | Max. 48 Watt, Standby 5 Watt |
| Dimensions | |
| Product | 441.6 x 460 x 44 mm / 17.4 x 18.1 x 1.73 inch |
| Packing | 590 x 687 x 120 mm / 23.2 x 27 x 4.7 inch |

Diagram (mm):

