

8U Rackmount 21.5" widescreen LCD display 1920 x 1080 with Digital TV Tuner ATSC(US Only), LED Backlight PIP, VGA + TV(ATSC) + HDMI + PC audio in + composite (RCA), w/ remote controller (Standard 2-year.Warranty)

Model: NPW8215TV



Basic I/O: HDMI, VGA, Composite, Audio TV w/ Remote controller



Display Features and Benefits

- 8U rackmount 21.5" widescreen LCD
- Full HD LCD display with 1080p resolution
- 16.7 million colors displayed in rich
- Digital TV tuner decodes ATSC signal
- HDMI, VGA, Composite (RCA) connection
- VESA and Rackmount multiple hole mounting
- Green LED technology ensures natural colors
- Modern touch controls

Specifications

LCD Panel

Manufacturer	Samsung
Size (diagonal)	21.5" widescreen TFT
Max resolution :	1920 x 1080
Brightness (cd/m2)	250
Colors	16.7M
Contrast ratio (typ)	1000 : 1
Viewing angle (H/V)	170° x 160°
Active area (mm)	477 x 268
MTBF (hrs)	30,000
Signal input	ATSC DTV / HDMI / VGA / Composite

Digital TV Tuner

Aerial input	75 ohm coaxial, I EC type
TV system	ATSC / NTSC

Sound

Weight

Net :	7.5 kgs / 16.9 lbs
Gross	10 kgs / 22 lbs

Environmental

Operating	0 to 50°C Degree
Storage	-5 to 60°C Degree
Relative humidity	5~90%, non-condensing
Shock	10G acceleration (11 ms duration)
Vibration	5~500Hz 1G RMS random vibration
Casing Color	Black front panel (RAL 9005) Dark grey rear case (RAL 7037)

Mounting

Rackmount, 8U
VESA mount, 100*100mm

Regulatory

FCC, CE, RoHS


Power

Input	Auto-sensing 100 to 240VAC, 50 / 60Hz
Consumption	Max. 48 Watt, Standby 5 Watt

Dimensions


Product :	501.9 x 64.4 x 353 mm / 19.8 x 2.5 x 13.9 inch
Packing	555 x 124 x 537 mm / 21.9 x 4.9 x 21.1 inch

VESA mount Installation



- Hardware and M4*4 pcs for VESA mount are not provided


Rear Mounting Bracket Installation



Step 1


- Mount the rear bracket with M6 screw set.
- 8 x M6 screw set are required.

M6 screw sets are not provided.




Step 2

- Insert the upper part of the NPW8215 display panel into the rear bracket



Step 3

- Push the lower part of the NPW8215 display panel into the rear bracket.




Step 4


- Fix the NPW8215 display panel into the rear bracket with two fasteners (Left & right side).
- Lock the NPW8215 display panel by the latch (on the bottom left & right side).

Drawings:


Front View





Left-side View



Rear View



Bottom View



Unit : mm