



2U Dual Slide 17" LCD Console Drawer
with 4K 3840 x 2160 Native Resolution

Model: NVP2417K

FEATURES:

- 2U 17" 4K LCD console drawer
- Dual slide - LCD and keyboard slide independently
- 3840 x 2160 native resolution / 16.7M colors (8-bit)
- 1920 x 1080 & 1920 x 1200 resolution support
- Display port 1.2 video input / USB KB / MS
- 104-key keyboard with either touchpad or trackball
- Built-in dual stereo speakers
- Short depth design of 480mm
- One Man installation design
- Enhanced aesthetics with molded front handle and two point lock
- 2-year standard warranty (upgradable up to 5 years)

OPTIONS

- HDMI 2.0 Video Input
- 3G / HD / SD-SDI Broadcast-grade input
- DC power : 12V / 24V / 48V / 125V
- MAC or SUN Micro keyboard options available
- Touchscreen : Projected Capacitive 10-pt / Resistive 1-pt

SPECIFICATIONS:

Console Port	
Video input	Display port 1.2
KB / MS	USB type B
DP console 6ft cable : NP-6	Drawer end : DP + USB type B (KB / MS) Server end : DP + USB type A

LCD Panel	
Panel size (diagonal)	17.3"
Native resolution	3840 x 2160
Brightness (cd/m ²)	400
Contrast ratio (typ.)	1000 : 1
Colors	16.7 M, 8-bit
Viewing angle (L/R/U/D)	89/89/89/89
Response time (ms)	30
Dot pitch (mm)	0.0995
Display area (mm)	382.12H x 214.94V
Surface treatment	Anti-glare
Surface hardness	3H
Backlight type	LED
MTBF (hrs)	20,000

Mounting Distance	
Single console drawer / Console w/ KVM drawer	490 ~ 700 mm 19.3 ~ 27.6 inch

Video Option		
Digital	HDMI	HDMI 2.0 / HDCP 2.2

Audio Option		
Output	Connector	3.5mm stereo jack
	Resistance / Power level	30kΩ / 2.8V
Speaker	Dual stereo	2W x 2

Power		
Input	Auto-sensing 100 to 240VAC, 50 / 60Hz	
Consumption (console / KVM)	Screen on	Max. 29W / Max. 38W
	Power saving mode	Max. 9W / Max. 18W
	Power button on	Max. 2W / Nil


Environment	
Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	20~90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration (11ms duration)
Vibration	10~300Hz 0.5G RMS random vibration

Compliance	
EMC	FCC & CE certified
Safety	CE / LVD certified
Environment	RoHS2 & REACH compliant

Physical		
Dimensions: (W x D x H)	Single console	442 x 480 x 88 mm 17.4 x 18.9 x 3.5 inch
	Console w/ KVM	442 x 480 x 88 mm 17.4 x 18.9 x 3.5 inch
Packing (W x D x H)	Single console / Console w/ KVM	585 x 620 x 190 mm 23 x 24.4 x 7.5 inch
	Net weight	Single console
Console w/ KVM		21.1 kg / 46.4 lb
Gross Weight	Single console	24.8 kg / 54.6 lb
	Console w/ KVM	27 kg / 59.4 lb

STANDARD KEYBOARD

e keyboard integrated with touchpad



b keyboard integrated with trackball




Supporting layouts

Region	Country	Country	Country	Country	Country
America	United States				
EMEA	United Kingdom	Germany	France	Spain	Norway
	Italy	Russia	Switzerland	Netherlands	Portugal
	China	Japan	Korea	Arabia	Turkey

NVP2417K MODELS W/ KVM

DP KVM	TP	Remote	12-port
	0	0	NVP2417K - 1201P

DP USB KVM Cable

Resolution Support :	16:10 - max. 1920 x 1200	
	16:9 - max. 3840 x 2160	
	4:3 - max. 1600 x 1200	
** Resolution related to LCD specification		NP - 6 (6 ft)

KEYBOARD OPTIONS (US layout only)

Me Mac keyboard with touchpad



Se S keyboard with touchpad



Mb Mac keyboard with trackball

Sb S keyboard with trackball