



Combo DB-15 KVM
Model: NVS801
NVS1601



Combo DB-15 KVM Benefits




- Combo DB-15 KVM with either 8 or 16 ports in 1U
- Cascade switches up to 8 levels & Mix switches between Cat6 & Combo DB-15 KVM
- Mix PS/2, USB & SUN with Multi-Platform switch capability
- Support native SUN 1152 x 900 resolution
- Hot pluggable, no software or drivers required
- Easy & quick installation

Designed for:



Switch Features & Options

- Multi lingual on screen display menu
- Advanced user profiles and configurable OSD hot key combinations
- Dual power with failover



Technical Specification

- **KVM Port :** 16 / 8 x DB-15 connector
- **KVM Cable :** Combo 4-in-1 KVM cable, up to 6, 10 & 15 feet
- **Local Console :** 1 x DB-15 VGA (up to 1600 x 1200), 2 x USB for KB & MS
- **Expansion :** Support mixed Combo Cat6 or Combo DB-15 KVM, up to 240 servers
- **Compatibility :** Mix PCs, SUNs, MACs, IBMs, HPs, DELLs server
Windows Vista / 2003 / XP / 2000, Linux, Netware, Unix
- **Power :** 100-240VAC, 50 / 60Hz 0.3A via IEC type cord (12V / 24V / 48V DC input option)
- **Regulatory Approval :** FCC, CE
- **Environmental**
 - Operating / Storage : 0 to 50°C / -5 to 60°C
 - Relative humidity : 90%, non-condensing
 - Shock : 50G peak acceleration (11 ms, half-sine wave)
 - Vibration : 58-100Hz / 0.98G (11 ms/ cycle)

Accessories

NE-6
NE-10
NE-15



Combo 4-in-1 KVM cable - 6, 10 & 15 ft

CBC-6



6ft Combo KVM cascade cable

Dimensions

Model	Product Dimension (W x D x H)	Packing Dimension (W x D x H)	Net Weight	Gross Weight
NVS801 NVS1601	446 x 180 x 44 mm 17.6 x 7.1 x 1.73 inch	510 x 400 x 77 mm 20.1 x 15.7 x 3 inch	4 kg / 9 lbs	7 kg / 15 lbs

Model: NVS801



Model: NVS1601

