

Multi Touch LCD Monitors

65" Wide Multi Touch LCD Monitor

Model: OCHW6500MOT



65" LED-Backlit Commercial Multi-Touch Display, using NEC V652, 6 Point Optical Multi-Touch Screen, USB Touch Screen Interface 1920 x 1080 Native Resolution, Narrow Front Bezel, 16:9 Aspect Ratio, 4000:1 Contrast Ratio, 450cd/m2 Max Brightness (Nits), 178 Degree Vertical/Horizontal Viewing Angle, Display Port/HDMI/ DVI-D/VGA/5 BNC/S-Video/Composite BNC Input Connectors, 400mm x 400mm VESA Mount, Black, Built In Speakers, OPS Expansion, No Stand, 3 Year Return to Depot Warranty

Features

- Using NEC Display Model V652
- Optical 6 Point Multi-Touch
- 1080p HD Resolution
- 3 Year Limited Warranty
- Internal 10W Speakers x 2

Product Specifications:

Size/Type	65 inch Diagonal/ Active Matrix LED Display
Touch Technology	Optical 6 Point Multi-Touch
Brightness	300cd/m2 (Typical), 450 cd/m2 (Max)
Contents of Packaging	User's Manual, AC Power cord, Wireless Remote, Batteries, 1.8m DVI-D cable, CD-ROM, Setup Sheet & Driver CD
Contrast Ratio	4000:1
Colors	more than 16.7 million (depending on video card used)
Optional	TV Tuner, Built-in PC, External Speakers, Stand
Dimensions (W x H x D)	Net (with stand): 60.6 x 37.2 x 20.2 in. / 1540.4 x 944.7 x 512mm Net (without stand): 60.6 x 35.8 x 3.5in. / 1540.4 x 909.2 x 88.3mm
Input	DVI-D w/ HDCP, Analog D-Sub, Analog BNC, Composite RCA, S-Video, HDMI, Display Port, Component BNC, RS232, DDC/CI, Audio1 (minijack), Audio 2 and 3 stereo (RCA)
Limited Warranty	3 year including backlight
Operating Altitude	3000m/9842.5 ft.
Operating Humidity	20-80%
Operating Temperature	5-40 C/41-104 F
Pixel Pitch	0.74mm
Power Consumption	On: 185W , Power Savings Mode: <2W
Resolutions Supported	640x480, 800x600, 1024x768, 1280x768, 1360x768, 1280x1024 1600x1200 @ 60Hz (Compressed), 1920x1080 @ 60Hz (Recommended)
Storage Altitude	12,192m / 40000 ft.
Storage Humidity	10-90%
Operating Temperature	-20-60 C/-4-140 F
VESA Hole Configuration Spec.	400 x 400 mm (4 hole)
Viewing Angle	Up 89 / Down 89 / Left 89 / Right 89 (typ.)
Voltage Rating	AC 100-120V / AC 220-240V @50/60 Hz
Weight	Net with stand: 126 lbs., Net without stand: 115 lbs.
Additional Features	Power Management Plug and Play (DDC/CI DDC2B) PIP (Remote) Multi level Zoom, FullScan, 6 axis color CableComp TileMatrix TileComp Screen Saver Rapid Response, Video Ready (no tuner) Infrared remote control included

iTechLCD, reserves the right to change any of the information contained on this document without notice. We also reserve the right to discontinue, limit production or distribution of this our any other iTechLCD product.

