

Model: OCH2100T-TCU

Features:

- * Using NEC Monitor Model LCD2190UXp-BK
- * Monitor can Tilt, Swivel and is Height Adjustable
- * Quick release stand & VESA mountable
- * Supports higher resolutions



Specifications:

Size	21 inch Diagonal
Type	Active Matrix LCD Display
Touch Technology	5-Wire Resistive or Capacitive
Brightness	300 cd/m2
Contents of Packaging	User's manual, Power cord, Setup Sheet, OWT Driver CD
Contrast Ratio	1000:1
Dimensions	Net (with stand): 18.3 x 16.7-22.6 x 9.7 in./ 464.8 x 424.8- 574.8 x 247.3mm Net (without stand) 18.3 x 14.1 x 3.3in./ 464.8 x 358.6 x 85.0mm
Display Colors	More than 16 million
Input	DVI-D DVI-I & VGA 15 pin D-sub
Operating Altitude	3,048m / 10,000 ft.
Operating Humidity	30 to 80%
Operating Temperature	5 to 35C/41 to 95F
Pixel Pitch	.270mm
Power Consumption	On: 52W Power Savings Mode: <1W
Resolutions Supported	640 x 400 @ 70-85 Hz (Digital) 720 x 400 @ 70-85 Hz 640 x 480 @ 60-85 Hz

	800 x 600 @ 56-85 Hz
	832 x 624 @ 75 Hz
	1024 x 768 @ 60-85 Hz
	1152 x 864 @ 70-85 Hz
	1152 x 870 @ 75 Hz
	1200 x 1600 @ 60 Hz
	1280 x 960 @ 60 Hz
	1280 x 1024 @ 60-85 Hz
	1600 x 1200 @ 60 Hz
Storage Altitude	12,192m / 40,000 ft.
Storage Humidity	10 to 85%
Storage Temperature	-10 to 60C/14 to 140F
Synchronization Range	Horizontal: 31.5-91.1 KHz (Analog) 31.5-99.4KHz (Digital) Vertical: 50.0-85.0 Hz
VESA Hole Configuration Spec.	100mm x 100mm
Viewing Angle	176 Vert. 176 Hor. (88U/88D/88L/88R) (CR>10)
Voltage Rating	AC 100-120V/AC 220-240V
Weight	(with stand) 23.6lbs./10.7 kg (without stand) 17.6lbs./ 8.0kg
Response Time	16ms
Additional Features	Ultra Thin-frame (bezel) No Touch Auto Adjust NaViSet software Tilt VESA Mount sRGB Cable Management Touch Enabled Swivel Vacation Switch Height-Adjustable Stand 12 Bit Gamma AmbiBright Pivot Color Comp Over Drive Eco-Mode Real Time Clock Quick Release Stand Ambix3



i-Tech Company LLC

TOLL FREE: (888) 483-2418 • EMAIL: info@itechlcd.com • WEB: www.iTechLCD.com