

Model: OCHW3200-DSTU

Features:

- * Using NEC Display Model LCD3215
- * Real-time clock for content scheduling
- * 1366 x 768 ultra-high resolution
- * Stand Not Included (Optional)



Specifications:

Size	32 inch Diagonal
Touch Type	DST (Dispersive Signal Technology)
Accessories	AC power cord, user manual, setup sheet, wireless remote control, batteries, 15-pin RGB cable CD-ROM, OWT Driver CD
Brightness	500 cd/m2 (typical)
Colors	256 RGB Level more than 16 million
Contrast Ratio	600:1
Dimensions	(WxHxD) Net (with stand) 31.1 x 20.1 x 7.9 in./789 x 510.3 x 200mm Net (without stand) 31.1 x 18.9 x 5.5 in./789 x 479 x 140mm
Input Signal	Video: ANALOG RGB Vp-p / 75 Ohms Sync: Separate sync: TTL Level (Positive/Negative) Composite sync: TTL Level (Positive/Negative) Composite sync on green: (0.3Vp-p negative 0.7Vp-p positive)
Input	RGB1: DVI-D x 1 RGB2: Analog D-sub RGB3: Analog BNC Video 1*: Composite RCA or S-Video Component Video 1 (DVD/HD): Component BNC Audio: Audio 1 (minijack) Audio 2 and 3 Stereo (RCA)

	Internal Speaker: None External Control: RS232 DDC/CI
Operating Humidity	20-80%
Operating Temperature	5-40° C/41-104° F
Pixel Pitch	0.511
Power Consumption	(typical) On: 140W Power Savings Mode: <5W
Regulatory Approvals	UL 1950/CSA C22.2 No. 950/TUV-GS/EN60950/FCC-B/ DOC-B/EN55022- B/EN55024/EN61000-3-2/EN1000- 3-3/CE
Resolutions Supported	720 x 400 @ 70-85 Hz 640 x 480 @ 60-85 Hz 800 x 600 @ 50-85 Hz 832 x 624 @ 74.5 Hz 1024 x 768 @ 50-85 Hz 1280 x 1024 @ 50-85 Hz 1600 x 1200 @ 60 Hz (Compressed) 1280 x 768 @ 50-85 Hz 1360 x 768 @ 50-85 Hz NTSC/PAL, SECAM, 4.43NTSC, Pal60 HDTV, 480i 480p, 720p 1080i
Storage Humidity	10-90%
Storage Temperature	-20-60° C/-4-140° F
Synchronization Range	31.5-91.1 KHz (15.625,15.734 kHz) (Analog) 31.5-91.1 KHz (Digital) Vertical: 58-85 Hz Analog / 50-85 Hz Digital
VESA Hole Configuration Spec.	200 x 200mm (8 hole) / 200 x 100mm (6 hole)
Viewing Angle	176° Vert. 176° Hor. (88U/88D/88L/88R)@ CR>10
Voltage Rating	AC 100-120V / AC 220-240V @ 50/60 Hz
Weight	(with stand) 37.5 lbs./17 kg (without stand) 35.3 lbs./16 kg
Additional Features	Power Management Plug and Play (DDC/CI DDC2B), PIP (Remote) Multi-level Zoom FullScan TileMatrix, TileComp Screen Saver Rapid Response Video Ready (no tuner) Infrared remote control included removeable stand included
Output	RGB: Daisychain RGB3 Video: Daisychain Video1 Audio: Daisychain - Selected Audio in Control: RS232 for multiple monitor control Audio Amplifier: 7W x 7W

