



	External Control: RS232 DDC/CI
<b>Operating Humidity</b>	20-80%
<b>Operating Temperature</b>	5-40° C/41-104° F
<b>Pixel Pitch</b>	0.511
<b>Power Consumption</b>	(typical) On: 140W Power Savings Mode: <5W
<b>Regulatory Approvals</b>	UL 1950/CSA C22.2 No. 950/TUV-GS/EN60950/FCC-B/ DOC-B/EN55022- B/EN55024/EN61000-3-2/EN1000- 3-3/CE
<b>Resolutions Supported</b>	720 x 400 @ 70-85 Hz 640 x 480 @ 60-85 Hz 800 x 600 @ 50-85 Hz 832 x 624 @ 74.5 Hz 1024 x 768 @ 50-85 Hz 1280 x 1024 @ 50-85 Hz 1600 x 1200 @ 60 Hz (Compressed) 1280 x 768 @ 50-85 Hz 1360 x 768 @ 50-85 Hz NTSC/PAL, SECAM, 4.43NTSC, Pal60 HDTV, 480i 480p, 720p 1080i
<b>Storage Humidity</b>	10-90%
<b>Storage Temperature</b>	-20-60° C/-4-140° F
<b>Synchronization Range</b>	31.5-91.1 KHz (15.625,15.734 kHz) (Analog) 31.5-91.1 KHz (Digital) Vertical: 58-85 Hz Analog / 50-85 Hz Digital
<b>VESA Hole Configuration Spec.</b>	200 x 200mm (8 hole) / 200 x 100mm (6 hole)
<b>Viewing Angle</b>	176° Vert. 176° Hor. (88U/88D/88L/88R)@ CR>10
<b>Voltage Rating</b>	AC 100-120V / AC 220-240V @ 50/60 Hz
<b>Weight</b>	(with stand) 37.5 lbs./17 kg (without stand) 35.3 lbs./16 kg
<b>Additional Features</b>	Power Management Plug and Play (DDC/CI DDC2B), PIP (Remote) Multi-level Zoom FullScan TileMatrix, TileComp Screen Saver Rapid Response Video Ready (no tuner) Infrared remote control included removeable stand included
<b>Output</b>	RGB: Daisychain RGB3 Video: Daisychain Video1 Audio: Daisychain - Selected Audio in Control: RS232 for multiple monitor control Audio Amplifier: 7W x 7W

