

Two View LCD Console Drawers

2U Rackmount Dual 2 x 19" LCD 1280 x 1024 integrated with 101-key pull out backlit keyboard and touchpad, Analog VGA x2, DVI-D x2, Operation temp: 0 to 50C, Storage temp: -20 to 60C Humidity: 10% - 90%, non-condensing, Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP, Physical Dimensions / Net Weights 448x80x 635mm (WxHxD) / 15.5KG

Model: OHK2D119e

OHK Series

- Optimize rack space
- Maximize rack monitoring



The Two View range of LCD console drawers is optimized for low profile (2U height) and design to save value rack space while increasing your video content capacity. The self-locking rails when in the fully extended open position and the ultra convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation. Available with Dual 19" A-Grade LCD panels in a side-by-side configuration to convey twice information ,support independent dual display or screen extension and mirror mode. Both of dual LCDs have independent DVI , VGA , Audio ,Composite Video input.

FEATURES:

- 2U Single rail with dual 19" LCD Monitor / keyboard / Mouse Drawer. to convey twice information.
- Each display support DVI ,VGA , Audio and Composite video input.
- Support independent , mirror and extend display mode.
- Build in 2x2w stereo speakers.
- Build in durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra convenience.



SPECIFICATIONS

LCD	Size	Dual 19"
	Backlight	LED
	Resolution	1280*1024
	Max.color	16.7M
	Luminance	250cd/m2
	View Angel (H/V)	170 / 160
	Contrast Ratio	1000 : 1
Input Signals	VGA	Push Button, OSD or Hotkey
	DVI-D	Yes, option for Remote IP Access
	Audio	USB & PS2
	Composite Video	500mm to 1100mm (rack cabinet front rails to rear rails)
	USB/PS2	100-240V AC 50/60Hz via IEC Type power cord
KB/Mouse Emulation		USB / PS2
Rack Depth		550mm to 1200mm (rack cabinet front rails to rear rails)
Power		100-240V AC 50/60Hz via IEC Type power cord
Environment		Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP
Physical Dimensions / Net Weights		448x80x 635mm (WxHxD) / 15.5KG
Packing Dimensions / Gross weights		550*210*780mm (WxHxD) / 21.0KG
Accessory		1.8meter IEC Type Power Cord x1 , 1.8meter VGA, DVI and AV Cable x 2, 1.8meter Audio Cable x 1 , 1.8meter USB Cable x 1 ,

MECHANICAL DRAWING:

