



10.4" Non-Touch Monitor  
True Flat Display with USB Interface  
(Glass Overlay)

MODEL: KKF1040B

## FEATURES AND BENEFITS

- High Strength Glass Overlay
- Durable Die-Casting Aluminum Base for Option
- 7", 8" and 10" Pole Base for Option
- USB or VGA Interface Available
- Easy for Installation - Only USB Cable Needed
- Spill Proof and Anti-Dust
- Best Choice for Space Limited Retail / Hospitality Settings
- True Flat Designed to Suit Harsh Environment



USB Interface Available



VGA Interface Available



True Flat Design



Wall Mount Available



Die-Casting Base for Option



7", 8" and 10"  
Pole Base for Option

## SPECIFICATIONS

Display Size	10.4"
Optimal Resolution	800 * 600
Panel Brightness	250 cd/m2 (typ)
Contrast Ratio	500:1 (typ)
Response Time	20 ms (typ)
Viewing Angle(L / R / U / D)	70 / 70 / 50 / 70
Tilt Angle	N/A
Input Video signal	USB Type
Power consumption	2.5W
Input Frequency	Horizontal: 31.5~60.2KHz Vertical: 56.3Hz~75Hz
Power supply	DC 5V +/- 10%
Temperature	Operating: 0°C~40°C (32°F ~ 104°F) Storage: -10°C ~ 50°C (14°F ~ 122°F)
Humidity	Operating: 20% ~ 80% Storage: 10% ~ 90%
Weight	0.85 Kgs (2.16 Lbs)
Physical Dimension WxHxD	244 * 197.4 * 36.4 (mm) 9.61 * 7.78 * 1.43 (inch)
Optional	White. Wall Mount Kit



### Accessories



USB Cable (for Touch model \*2)



Driver CD

## MECHANICAL DRAWINGS:

