

KK Series TOUCH Monitor

15" Resistive ELO Touch Monitor
with D-Sub 15 pins/ DVI-D

MODEL: KKF1500-TR

FEATURES AND BENEFITS

- Smart Cable Management
- Detachable Stand / Support VESA mounting
- Spill Proof & Anti-Dust
- Support 2nd Display & MSR
- Resistive Touch
- True Flat Designed to Suit Harsh Environment
- Project Capacitive Touch



MSR for Option



Smart Cable Management



Support 2nd Display



Spill proof of Front Panel



SPECIFICATIONS

Display Size	15"
Optimal Resolution	1024 * 768
Panel Brightness	250 cd/m2 (typ)
Contrast Ratio	500:1 (typ)
Response Time	8 ms (typ)
Viewing Angle(L / R / U / D)	160. (H)/160. (V)
Touch Function	ELO touch (USB or RS232 Interface)
Input Video signal	D-Sub 15 pins/ DVI-D
Power consumption	20W Operation 3W Standby
Input Frequency	Horizontal: 31.5 ~ 60.2 kHz Vertical: 56.3Hz ~ 75Hz
Power supply	DC 12V +/- 10%
Temperature	Operation: 0°C ~ 40°C (32 F ~ 104F) Storage: -10°C ~ 50°C (14 F ~ 122F)
Humidity	Operation: 20% ~ 80% Storage: 10% ~ 90%
Weight	4.67Kgs (10.3Lbs)
Physical Dimension	365.2 * 338.6 * 200 (mm)
WxHxD	14.38 * 13.33 * 7.87 (inch)
Optional	2nd Display, Wall Mount, White Color MSR, Front Bezel Design

Accessories



VGA Cable



Touch Driver / Manual CD



Power Adapter



Power Cable



Touch Cable USB or RS232

MECHANICAL DRAWINGS:

