

Plastic case, True Flat 10.4" LCD monitor with Resistive Touch USB controller, USB video input 800 x 600, 250 nits, 500: 1 244\*197\*36(mm) 96.1\*77.6\*14.2(inch) 1.1Kgs (2.42lbs)



## Model: OTP1040B

### FEATURES

- Support Resistive Touch
- USB or VGA Interface Available Optional Die-Casting Aluminum Base
- Easy for Installation - One USB Cable Needed
- Best Choice for Space Limited Retail / Hospitality Settings
- Spill Proof and Anti-Dust



USB Interface Available



VGA Interface Available



75 x 75mm VESA Wall Mount



Optional Die-Casting Stand

### Technical Specifications

<b>Display Size</b>	10.4"
<b>Optimal Resolution</b>	800 x 600
<b>Panel Brightness</b>	250 cd/m2 (typ)
<b>Contrast Ratio</b>	500:1 (typ)
<b>Response Time</b>	20 ms (typ)
<b>Viewing Angle (L/R/U/D)</b>	70 / 70 / 50 / 60
<b>Tilt Angle</b>	N/A
<b>Input Video signal</b>	USB B Type
<b>Touch</b>	Resistive Touch, USB interface
<b>Power consumption</b>	2.5W
<b>Input Frequency</b>	Horizontal: 31.5-60.2 kHz ; Vertical :56.3Hz~75Hz
<b>Power supply</b>	DC 5V +/- 10%
<b>Temperature</b>	Operating : 0°C~40°C ; Storage : -10°C~50°C
<b>Humidity</b>	Operating : 20%~80% ; Storage : 10%~90%
<b>Weight</b>	1.1 Kgs (2.42lbs)
<b>Physical Dimension WxHxD</b>	244*197*36(mm) 96.1*77.6*14.2(inch)
<b>Optional</b>	White, Wall Mount Kit, Stand

\* This specification is subject to change without prior notice.



## MECHANICAL DRAWING

