Touch LCD Monitors

17" Capacitive Touch LCD Monitor Model: OCH1700SP-TCU



Features

- Using NEC Model LCD175VX
- Choice of Black or White Cabinet
- 3 Year Limited Warranty



Size/Type 17 inch Diagonal/ Active Matrix LCD Display

Touch Technology Resistive, Capacitive, or SAW

Brightness (typical) 270 cd/m2

User's Manual, Power cord, Setup Sheet & Driver CD Contents of Packaging

Contrast Ratio (typical) 600:1

Net (with stand): 14.5 in. (W) x 14.1-16.1 in. (H) x 9.1 in. (D) **Dimensions**

368 mm (W) x 358.5-408.5 mm (H) x 230 mm (D) Net (without stand): 14.5 in. (W) x 12.6 in. (H) x 2.4 in. (D)

368 mm (W) x 320.5 mm (H) x 61 mm (D)

Display Colors More than 16 million

(Dependent upon display card used)

Input Video Signal ANALOG: 0.7 Vp-p/75 Ohms

Input DVI-D and VGA 15 pin D-sub 3 Years Parts and Labor including Backlight

Limited Warranty

Operating Altitude 3048m / 10,000 ft.

Operating Humidity 30-80%

Operating Temperature 5-35°C / 41-95°F **Pixel Pitch** 0.264 mm **Power Consumption** On: 30W

Power saving mode: 2W

720 x 400 at 70 Hz - 1280 x 1024 @60 Hz **Resolutions Supported**

12,192m / 40,000 ft. Storage Altitude

Storage Humidity 10-85%

Storage Temperature -10-60°C / 14-140°F

Separate Sync: TTL Level (positive/negative) Sync Synchronization Range Horizontal: 31.5 kHz to 81 kHz (Analog/Digital)

(Automatic) Vertical: 56 Hz to 76 Hz

VESA Hole Configuration Spec. 100mm x 100mm

Viewing Angle (typical)

170° Vert. 176° Hor.

(85U/85D/88L/88R) (CR>5)

Voltage Rating 100-240V@ 50/60Hz Weight Net: 10.6 lbs. / 4.8 kg

Net (without stand): 8.4 lbs. / 3.8 kg

Additional Features Thin-frame (bezel), tilt, No Touch Auto Adjust, cable management, touchscreen compatible,

NaViSet software, digital smoothing, digital controls, user (OSD) controls, Plug and Play (VESA DDC 1/2B), Accu-Color color control, DDC/CI, VESA DPMS power management, ISO 13406-2

Class II, Windows Vista Certified

Response Time (typical) Rapid Response (5ms)





