

# Multi Touch Monitor

24" Wide LED Touch Monitor, using NEC P243W-BK, 5-Wire Resistive Single-Touch with ELO Touch Controller, USB Interface, 1920 x 1200 Native Resolution, 16:10 Aspect Ratio, 1000:1 Contrast Ratio, 350cd/m2 Typical Brightness (Nits), 178 Degree Vertical/Horizontal Viewing Angle, VGA/Display Port/DVI-D/HDMI Input Connectors, Removable Stand, 100mm x 100mm VESA Mount, Black, 3 Year Return to Depot Warranty

**Model: OCHW2400HD-ELO-V2**



## FEATURES:

- Using NEC Monitor P243W-BK
- 5 Wire Resistive Single Touch w/ ELO Controller & Drivers, USB Interface
- Tilt, Swivel or Height Adjustable
- 3 Year Parts & Labor Warranty

## PRODUCT SPECIFICATIONS:

<b>Size/Type</b>	24.1 inch Diagonal/ IPS Panel with LED Backlighting
<b>Touch Technology</b>	5 Wire Resistive (Single Touch ) with ELO Controller & Drivers, USB Interface
<b>Brightness</b>	350 cd/m2 (Nits)
<b>Resolution</b>	1920 x 1200
<b>Contents of Packaging</b>	User's Manual, Power Cord, Video Cable(s), Setup Driver CD
<b>Aspect Ratio</b>	16:10
<b>Contrast Ratio</b>	(typical) 1000:1
<b>Dimensions (W x H x D)</b>	Net (with stand): 21.9 x 14.9-20.8 x 9.2 in./ 556.3 x 378.5-528.3 x 233mm Net (without stand): 21.9 x 14.2 x 2.3in./ 556.3 x 361.8 x 56.8mm
<b>Display Colors</b>	1.07 billion
<b>Input</b>	DisplayPort, DVI-D, HDMI & VGA 15 pin D-sub & USB B Ported (for Touch)
<b>Limited Warranty</b>	3 Years Parts and Labor including Backlight
<b>Operating Altitude</b>	5,000m / 16400 f.
<b>Operating Humidity</b>	20 to 80%
<b>Operating Temperature</b>	5 to 35C/41 to 95F
<b>Pixel Pitch</b>	.270mm
<b>Power Consumption</b>	On: 25W, Power Savings Mode: .2W
<b>Storage Altitude</b>	12,192m / 40,000 f.
<b>Storage Humidity</b>	10 to 85%
<b>Storage Temperature</b>	-10 to 60C/14 to 140F
<b>Synchronization Range</b>	Horizontal: 31.5-93.8/118.4 KHz Vertical:50.0-85.0 Hz
<b>VESA Hole Configuration Spec.</b>	100mm x 100mm
<b>Viewing Angle</b>	178 Vert. 178 Hor. (89U/89D/89L/89R) (CR>10)
<b>Voltage Rating</b>	AC 100-120V / AC 220-240V
<b>Weight</b>	(with stand) 19.5 lbs./8.84 kg (without stand) 13.4 lbs./ 6.07 kg
<b>Response Time (typical)</b>	8ms
<b>Additional Features</b>	ECO Mode, Ultra Thin-bezel, No Touch Auto Adjust, NaViSet software, Tilt, Swivel, Pivot, Height Adjustable, Quick Release Stand, Carrying Handle, Cable Management, OSD User Controls, 14 Bit 3D LUT, AmbiBright, CableComp, Carbon Footprint Meter, Rapid Response, XtraView+, HDCP, DDC/CI, Black Level Adjustment, GammaComp MD QA Software, SpectraView Software Ready

**DRAWING:**

