Metered PDU
BPM Series

Data Center Power Metering Pollable via RS232

- Network-grade Power Distribution for UL 60950-1 Branch Circuit Protection
- True RMS Current Metering per In-Feed & Branch Circuit
- Data Center Power Polling via RS232
- 3-Digit LED Digital Amp Load Display
- 80% Threshold Alarming

- ✓ 5 Year Warranty
- ✓ Stocked for Same Day Shipments
- ✓ In-House Design & Manufacturing
- ✓ Made In USA

Model BPM-24VS20-2

Distribute power to network equipment at the rack level, balance current loads and prevent tripped circuit breakers!

The BPM Series PDU uses true RMS current metering to display total amperage load per in-feed and on each branch circuit. An invertible LED display option allows you to read current load when the unit is mounted upside-down for overhead power delivery to the rack. Threshold alarms indicate 80% load capacity per in-feed or branch circuit.

The BPM Series PDU comes in a variety of models to accommodate your power distribution needs. Using UL 489 circuit breakers to comply with UL 60950-1 standards and quality manufacturing techniques. WTI provides a metered PDU built and delivered with the same level of quality, service and support as our other industry leading products.

Pollable via RS232

Model BPM-24VS20-1

- 8/16/24 Outlets
- 20/30 Amp Single Phase 100/250V AC
- 20 & 30 Amp 208V 3-Phase
- Always On Outlets
- Vertical Toolless Mounting

Model BPM-16VS20-1

Model BPM-8HVS20-2

Metered & Switched PDU

Metered PDU
BPM Series

Model Number	Outlets	AC Voltage 50/60 Hz	Power Distribution (80% Derated)	Input Feed	Power Cord (Sold Separately) Lengths and Styles Vary	Dimensions L"xW"xD"
Horizontal/Vertical Mounting						
BPM-8HS20-1	(8) NEMA 5-20R	85 - 125V	1.4 - 2 kW	20 Amp	Detachable	17x1.75x3.31
BPM-8HS20-2	(8) IEC 60320 C13	200 - 250V	3.2 - 4 kW	20 Amp	Detachable	17x1.75x3.31
Vertical Mounting						
BPM-16VS20-1	(16) NEMA 5-20R	85 - 125V	1.4 - 2 kW	20 Amp	Detachable	32x1.95x3.1*
BPM-16VS20-2	(16) IEC 60320 C13	200 - 250V	3.2 - 4 kW	20 Amp	Detachable	32x1.95x3.1*
BPM-16VS30-1	(16) NEMA 5-20R	85 - 125V	2 - 3 kW	30 Amp	Fixed - NEMA L5-30P	32x1.95x3.1*
BPM-16VS30-2	(16) IEC 60320 C13	200 - 250V	4.8 - 6 kW	30 Amp	Fixed - NEMA L6-30P	32x1.95x3.1*
BPM-24VS20-1	(24) NEMA 5-20R	85 - 125V	1.4 - 2 kW	20 Amp	Detachable	52x1.95x3.1*
BPM-24VS20-2	(24) IEC 60320 C13	200 - 250V	3.2 - 4 kW	20 Amp	Detachable	52x1.95x3.1*
BPM-24VS30-1	(24) NEMA 5-20R	85 - 125V	2 - 3 kW	30 Amp	Fixed - NEMA L5-30P	52x1.95x3.1*
BPM-24VS30-2	(24) IEC 60320 C13	200 - 250V	4.8 - 6 kW	30 Amp	Fixed - NEMA L6-30P	52x1.95x3.1*
Vertical Mounting 3-Phase						
BPM-24VS20-D	(24) IEC 60320 C13	208V 3Ø	5.7 kW	20 Amp	Fixed - NEMA L15-20P	52x1.95x3.1*
BPM-24VS20-Y	(24) IEC 60320 C13	208V 3Ø	5.7 kW	20 Amp	Fixed - NEMA L21-20P	52x1.95x3.1*
BPM-24VS30-D	(24) IEC 60320 C13	208V 3Ø	8.6 kW	30 Amp	Fixed - NEMA L15-30P	52x1.95x3.1*
BPM-24VS30-Y	(24) IEC 60320 C13	208V 3Ø	8.6 kW	30 Amp	Fixed - NEMA L21-30P	52x1.95x3.1*

*** 3.1" maximum depth**

- Multiple Branch Circuits per In-Feed
- Zero U Vertical & 1U Horizontal Mounting
- Universal & Toolless Mounting Brackets
- Detachable & Fixed Input Cords

Model BPM-24VS30-1

Metered & Switched PDU

i-TECH COMPANY
Distributed by: i-Tech Company LLC
TOLL FREE: (888) 483-2418 • EMAIL: info@i-techcompany.com • WEB: www.iTechLCD.com