

FANLESS Industrial Panel PC

Fanless Industrial Panel PC 27" LED TFT LCD, Intel Core 7th Generation i7 7600U 2.8 GHz / 3.9 GHz, 2 x DDR4-2133 SO-DIMM, Max 32GB (Non-ECC) w/ Projected Capacitive Touch Screen

Please specify Memory, Storage and OS when ordering.

MODEL: QPCW2700-i7



FEATURES

- 27" M grade LED LCD panel for long life cycle and your tough working environments
- Different Display Modules for every project requirements
- Modularized Design for different application needs and minimal system down time during maintenance
- Solid and rugged Display Construction withstands punishments from all environments
- True Flat multi Touch with front side IP65 certification
- Hidden USB to protect USB Key/Dongle
- 4 Different mounting methods designed in for ultimate application flexibility

SPECIFICATIONS:

Display Module	27"
I/O	1 x USB 2.0 Hidden for USB Dongle
Touch screen	Projected Capacitive Touch
LCD	27" TFT XVGA
Resolution	1920 x 1080, 16.2M Colors
Luminance (cd/m2)	300
Viewing Angle	178°
Backlight Lifetime	30,000hrs/ LED
Mechanical	
Construction	Heavy-duty steel chassis (Black), Aluminum Front Bezel
Vibration	5-17Hz, 0.1" double amplitude peak to peak, 1.5G acceleration peak to peak
Shock	10G acceleration peak to peak (11ms) ;
Rating	IP 65 compliant front bezel
Qualification	Formal certification CE I FCC Class B
Mounting	Panel / VESA 100 / Wall / Clamp Type
Optional Order	
Mounting	Clamp Type Mount

PC SPECS:

System Box Module	
Processor	Intel® Core™ 7th Generation i7 7600U 2.8 GHz / 3.9 GHz
System Memory	2 x DDR4-2133 SO-DIMM, Max 32GB (Non-ECC)
Storage	2.5" SATA HDD / mSATA SSD
I/O	Serial port x 4 (RS232/422/485 x 1, RS232 x 3)
	USB x 6 (USB 3.0 x 4, USB 2.0 x 3)
	Ethernet, RJ-45, PCI-e Gbe LAN x 2
	HDMI 1.4a x 1, DisplayPort 1.2 x 1
	Line in x 1, Line out x 1, Phone Jack
Expansion Interface	Mini PCI x 1
OS Support	Microsoft Windows 7/ 10, Linux
Power Requirement	DC Jack, +9V- +24V, Wide Range Input
Mechanical	
Construction	Heavy-duty steel chassis (Black), Aluminum Heatsink
Operation Temp.	32°F ~ 140°F (0°C ~ 60°C) with Ambient Air
Storage Temp.	-22°F ~ 175°F (-30°C ~ 80°C)
Relative Humidity	10~90% @40°C, Non-condensing
Backlight Lifetime	50,000hrs / LED
Vibration	5-17Hz, 0.1" double amplitude peak to peak, 1.5G acceleration peak to peak
Shock	10G acceleration peak to peak (11ms)
Rating	IP 65 compliant front bezel
Qualification	Formal certification CE/FCC Class B
Mounting	Panel/ VESA 100/ Wall/ Clamp Type
Dimension	128 x 64.4 x 268 mm
Packing Dimension	580 x 180 x 420 mm
System Weight(N.W.)	2.0 KG
Weight with Packing(G.W.)	3.2 KG
Optional Order	
Memory	DDR4 2GB, DDR4 4GB, DDR4 8GB, DDR4 16GB
Storage	2.5" SATA HDD 500GB~1TB, SSD 16GB~256GB
OS	Microsoft Windows 7/ 10, Linux
Wif LAN	RTL8188CUS-BC8-WB
Power	DC to Power Terminal Connector



DRAWINGS:

Not Available

