

## **RDC-3000**

## **Rackdrawer Keyboard with Pointing Device**

Ruggedized rackdrawer keyboards from iKey corner the market on rackmount p eripherals. The RDC-3000 offers the benefit of an integrated ruggedized HulaPoint™ pointing device. Standard size units have 14-inch rails (15-inch-deep d rawer) and come with chrome handle or pull slot options. Larger size units have 16-inch rails (17-inch drawer) and come with T-handle or locking T-handle options. The drawers have a CRS steel construction, which is coated with black epoxy paint, and chrome-plated, ball-bearing slides. (Model shown in photo is the T-handle option, part number RDC-3000-16-T)



## **Technical Specifications**

Certifications NEMA 12 UL60950, FCC Part 15 Class B

Shock 3x11 ms pulses of 50g on each of 3 axes

Cable LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2 or AT/serial Cable (providing separate keyboard and mouse

connections)

Key Switch MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 ACTUATION FORCE: 200g (+/- 20g)

FEEDBACK: Tactile with mechanical snap

Vibration POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3

hours

Power KEYBOARD: 5V@ 10 ma (from CPU port) HULAPOINT: 5V@ 10 ma (from mouse conn. port)

Flammability PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94 HB INTERFACE CABLE: 94 VO

Compatability PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems

Temperature Range STORAGE: -40C to +90C OPERATING: -40C to +70C

Weight 16 lbs (7.36 kg)

Warranty 1 year limited warranty

Humidity 100%

Dimensions Pull Slot/Chrome Handle: 19" x 15" x 1U (1.75") (w-h-d) 482.6mm x 381mm x 44.5mm T-handle: 19" x 17" x 1U (1.75")

482.6mm x 431.8mm x 44.5mm

Model Numbers

## **Features and Benefits**

Integrated HulaPoint Pointing Device
Slide Load Rating: 130 Lbs/Pair

USB, PS/2 and AT/serial configurations available





