# **OUTDOOR FILMING MONITOR**

21.5" Outdoor Filming Monitor High Brightness 1200nits, Video-IN: 3G-SDI, HDMI, Video-OUT: 3G-SDI

## Model: RCHW2150HB



### **FEATURES:**

- Screen Size: 21.5"
- High Brightness
- Providing 1200 nits of brightness, ideal monitor for outdoor filming.
- Practical, simple, and accurate operating system and functions.
- Capable of being adapted in both production and post-production stages.

#### **SPECIFICATION**

PANEL		
Size	21.5" LCD Monitor	
Resolution	1920 H x1080	
Dot Pitch	0.247 x 0.247mm	
Aspect Ratio	16:9 / 4:3 switchable	
Back Light	White LED	
Brightness	1200cd/m <sup>2</sup>	
Color Depth	8 Bits(16.7M)	
Contrast(Max)	1000:1	
Image Processing	10 Bits	
Response Time	7 ms	
Viewing Angle	H 178° / V 178°	
VIDEO IN		
3G-SDI	BNC x2	
HDMI	HDMI 1.3 x1	
VIDEO OUT		
3G-SDI	BNC x1	
AUDIO		
Audio demultiplexing	Support	
Audio meters	16 channels (Maximum 8 channels can be displayed at one time)	
Speakers	2x8Ω/2W (Back)	
Headset	3.5mm Support	
SDI Embedded Audio	Support	

\*Specifications subject to change without notice, not responsible for typographical errors.



VIDEO FORMAT	
HDMI	480p/60、480i/60、576i/50、576p/50、720p/50/60、1080i/50/60、1080p/24/25/30/50/60
3G-SDI	1080p(50/60)
HD-SDI	1080i(60/59.94/50)1080p(30/29.97/25/24/24sF/23.98/23.98sF)720p(60/59.94/50/30/29/25/24/23.98)
SD-SDI	480/59.94i、576/50i

#### OPERATION Input voltage 12V DC 4 pin XLR Power consumption(MAX) ≤25W Working temperature 0-40°C Store temperature -20-60°C Store humidity 0%-90% No Condensation

STRUCTURE		
Shell material	Aluminum Alloy	
Dimension(mm)	L514.8xH328xD40mm	
Weight(without battery)	Around 4.7KG	
Installing way	Desktop or VESA	
Mounting Holes	100x100mm	
Shipping Weight	14.5KG	



- 1. POWER SWITCH
- 6. LOCK KEY
- 2. MULTIFUNCTIONAL KNOB 7. HEADPHONE JACK
- 3. MENU

- 8. BOTTOM SUPPORT STAND
- 4. F1~F3 SHORTCUT KEY 9. BRIGHTNESS DETECTOR
- 5. SIGNAL SELECTION KEY



14. SOFTWARE UPGRADE PORT

MOUNTING HOLE

