

PORTABLE LCD MONITOR

7" Portable LCD Monitor, 1920 x 1200, 1000:1
Video Input 3G-SDI BNC x1, HDMI 2.0 Type A x1, 3G -SDI BNC x1

Model: RCMW700HD



FEATURES:

- Monitor that can measure light, only one second, real-time reproduction signal.
- Original closed detection technology expands the professional use of the monitor, assisting lighting sects to reduce cloth error rate.
- A new generation of light refractive gathering technology is used. The light intensity is under 100000lux, and it is still necessary to display a clear picture without the need to make the cover.

SPECIFICATION

PANEL	
Size	7 inch
Resolution	1920(H)x1200(V)
Dot Pitch	0.07875(H)x0.07875(V)mm
Aspect Ratio	16:9 / 4:3 switchable
Back Light	White LED
Brightness	100cd/m ² (max 500cd/m ²)
Color Depth	8 Bits(16.7M)
Contrast(Max)	1000:1
Image Processing	10 Bits
Response Time	7 ms
Viewing Angle	H 178° / V 178°

VIDEO IN	
3G-SDI	BNC x 1
HDMI	HDMI 2.0 Type A x 1 (Support 4K 60Hz)

VIDEO OUT	
3G-SDI	BNC x 1
HDMI	HDMI 2.0 Type A x 1

AUDIO	
Audio demultiplexing	Support
Audio meters	16 channels
Speakers	2x8Ω/2W
Headset	3.5mm Support

**Specifications subject to change without notice, not responsible for typographical errors.*

VIDEO FORMAT	
HDMI	2160/24p/30p/50p/60p、1080/24p/24psf/25p/30p/50i/60i/50p/60p、720/50p/60p、480i/480p、576i/576p
3G-SDI	1080/24p/24psf/25p/30p/50i/60i/50p/60p、720/50p/60p、480i/576i
HD-SDI	1080/24p/24psf/25p/30p/50i/60i、720/50p/60p、480i/576i
SD-SDI	480i/ 576i

OPERATION	
Input voltage	DC 12V / Battery 14.4V
Power consumption(MAX)	≤15W
Working temperature	-10-45°C
Store temperature	-20-60°C
Store humidity	0%-90% No Condensation

STRUCTURE	
Shell material	ABS
Dimension(mm)	192mm x 132mm x 27.5mm
Weight(without battery)	Around 0.45KG