






Foldable Sunhood

New generation super deep sunhood allows you get ideal view effect in almost all the environment.





BP battery holder



Anton battery holder



Convenient battery connector

Preset external battery connector could connect Sony and Anton battery plate on the back of the monitor. A 14.4V/100Wh video camera battery could support RD710S work over 8 hours.



Wide color gamut LCD panel and 1280×800 resolution ensure the monitor more precise color restoration , exquisite picture quality and more rich color levels.



i-Tech Company LLC

TOLL FREE: (888) 483-2418 • EMAIL: info@iTechLCD.com • WEB: www.iTechLCD.com











RD710S not only set up pixel to pixel, blue screen, monochrome, aspect ratio, etc function keys, but also reserves the knob for professional users. Double functions and knob type coding switch are iTechLCD's exclusive technology feature, which will bring you more convenient and rapid operate feeling.





















Specification:

Screen Size	7"		
Resolution	1280 (H) ×800 (V)		
Dot Pitch	0.117 (H) ×0.117 (V) mm		
Aspect Ratio	16:9 / 4:3 Switchable		
Brightness	400cd/m ²		
Contrast	800:1		
Response Time	12 ms		
Viewing Angle	H 178° / V 178°		
Voltage Input	DC12V		
Voltage Range	DC 6~36V		
Power Consumption	≤11W		
Monitor Size	L 207×H 147×D 38.5 mm		
Weight	≤1 kg		

Inputs & Functions:

	Model Function	RD710HD	RD710S	RD710	Remark
Video input	Composite	•	•	•	BNC×1 line 1.0 Vp-p±3 dB
	Component (Y/Pb/Pr)	•	•	•	BNC×1 line
	SD-SDI	•	•		BNC×1 line
	HD-SDI	•			BNC×1 line
	HDMI	•	•	•	HDMI×1 line
Audio input		•	•	•	RCA×1 line (dual channel)
Audio Monitoring		•	•	•	Front Speaker 0.5W (8Ω) Earphone:3.5mm jack
SDI Embedded Audio		•	•		PPM / UV
Video output	Composite	•	•	•	BNC×1 line Loop through 75Ω automatic termination
	Component (Y/Pb/Pr)	•	•	•	BNC×1 line
	SD-SDI	•	•		BNC×1 line
	HD-SDI	•			BNC×1 line
TALLY		•	•	•	Red/green two colors

Mechanical Drawing:

