



**Model: RPM1700**

# 17" Panel Mount Color Display Flat Panels

## Engineered Solutions

Industrial applications may be the most demanding environment for LCD's and flat panel displays. Whether your requirement is for a display for your console, an HMI, a CRT replacement or any factory automation process, i-Tech has the product for you. Combining our engineering expertise with the latest in flat panel display technology, finding the right options for your unique application is simple. The panel mount LCD offers rugged construction, superior image quality, extended product life cycle, rear controls and agency certifications. Select optional touch screens, protective glass and films, NTSC/PAL and S-Video connections, brightness enhancements, NEMA or VESA mounting solutions. i-Tech can customize your panel mount display providing custom colors, private labels, silk-screens, special power requirements and customized warranty and service programs.

- A-Si Active Matrix TFT Color LCD Panel
- VGA and DVI connections, optional NTSC/PAL, S-Video
- Lightweight but rugged design
- Perfect for VARs, System Integrators and OEM's
- Optional Touch Screen - Capacitive, Resistive or SAW
- Available with Protective Shields (AR/AG or Clear) or Privacy Shields
- Detects the sync type (separate, composite or sync on green automatically)
- Superb Quality - clear, bright, high contrast ratio with wide viewing angle



## Specifications

### RPM1700

LCD Size	17.0"
Standard Resolution	1280 x 1024
Pixel Pitch	0.264 mm
Pixel Arrangement	RGB Vertical Stripe
Brightness (typical)	420 cd/m <sup>2</sup>
Contrast Ratio	500:1
Aspect Ratio	4:3
Response Time (typical)	8 ms
Viewable Area	337.920 mm (H) x 270.336 mm (V)
Horizontal Viewing Angle	140°
Vertical Viewing Angle	140°
Color Depth	16.2 Million
Input Signal	Analog
Input Connector	15Pin D-Sub, Optional NTSC/PAL, S-Video, DVI
Frequency Range	30KHz - 80KHz (H)50Hz - 75Hz (V)
Power Supply Input (external)	DC 12V, 100 - 240V, 50 - 60Hz
Power Supply Output (external)	12V @ 4.16A
Power Consumption	12VDC @ 3.0A
Lamp Life	50,000 Hours
Operating Environment	0°C - 50°C
Relative Humidity	8% - 90% non-condensing
Storage Environment	-20°C - 60°C
Relative Humidity	8% - 90% non-condensing
Operating Altitude	10,000 Feet
Storage Altitude	30,000 Feet
Dimensions (WxHxD)	18.88" x 15.13" x 1.94"
Gross Weight	14 lbs
Color	Black or Custom
Warranty	1 Year



**Model: RPM1700**

# 17" Panel Mount Color Display Flat Panels

