

SK-102-461

Military Grade Mobile Keyboard with HulaPoint™

Designed to meet MIL-STD-461 standards, iKey's SlimKey™ SK-102-461 is ideal for use in rugged or harsh environments where electromagnetic interference is a top concern. In addition the SK-102-461 provides full-size versatility in a rugged, compact design, with the added convenience of an integrated HulaPoint™



The SlimKey™ SK-102-461 is engineered to meet NEMA 4X specifications, and is resistant to sand, debris and the elements. The large numeric pad on the SK-102-461 allows for easy data entry, while the robust polycarbonate case is durable in the roughest of environments.

Technical Specifications


Certifications	NEMA 4X UL60950, FCC Part 15 Class B
Shock	3x11 ms pulses of 50g on each of 3 axes
Cable	LENGTH: 10' straight (3 m)
Key Switch	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz +/- 1.06 oz (200g +/- 30g) FEEDBACK: Tactile with mechanical snap
Vibration	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
Power	PS/2: KEYBOARD: 50mA@5V (from Keyboard port) HULAPOINT: 35mA@5V (from Mouse port) USB: 85mA@5V (from CPU port)
Flammability	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94HB
Compatibility	PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
Weight	1.50 lbs +/- 0.10 lbs (0.68 kg +/- 0.05kg)
Warranty	1 year limited warranty
Humidity	100%
Dimensions	14.60" x 5.55" x 1.05" (w-h-d) 370.8mm x 141mm x 26.7mm

Features and Benefits

- 12 Function Keys
- Integrated HulaPoint Pointing Device
- USB and PS/2 configurations available
- Designed to meet MIL-STD-461E Specifications
- MS Windows Function Keys

SK-102-461

DATE	CHANGES	INTL	REV
12.16.11	Original	TH	1.00



KEY SWITCH

MATERIAL: Industrial Silicone Rubber
 LIFE: Greater Than 10 Million Cycles
 TRAVEL: 0.055 in.
 ACTUATION FORCE: 7.05 oz. +/- 1.06oz (200g +/- 30g)
 FEEDBACK: Tactile with Mechanical Snap

TEMPERATURE RANGE

STORAGE: -40°F to +194°F (-40°C to +90°C)
 OPERATING: -40°F to +158°F (-40°C to +70°C)

VIBRATION

POWER SPECTRAL DENSITY: .04g/HZ
 FREQUENCY RANGE: 20Hz-2Khz
 DURATION OF TEST PER AXIS: 3 hours

POWER

PS2: KEYBOARD: 50mA@5V (from Keyboard port)
 POINTER: 35mA@5V (from Mouse port)
 USB: 85mA@5V (from CPU port)

HUMIDITY

100% Humidity Resistant

SHOCK

3 X 11 ms pulses of 50g on each of 3 axis

WEIGHT

1.50 lbs +/- 0.10 lbs (0.68 kg +/- 0.05 kg)

PROPRIETARY AND CONFIDENTIAL

SCALE: 1:2

Part Number: SK-102-461	Drawing Number: MKT0299	Sheet: 1 OF 1
Drawing Title: SK-102-461-MKT	Revision: 1.0	Date: 12.16.11 TWH



Distributed by:
 i-Tech Company LLC
 TOLL FREE: (888) 483-2418 • EMAIL: info@iTechLCD.com • WEB: www.iTechLCD.com