

# SLK-102-461

## Designed to meet MIL-STD-461 standards

Designed to meet MIL-STD-461 standards, iKey's SlimKey® SLK-102-461 is ideal for harsh environments where electromagnetic interference is a top concern. In addition the SLK-102-461 provides full-size versatility in a rugged, compact design, with the added convenience of an integrated HulaPoint II®. The SlimKey® SLK-102-461 is engineered to meet NEMA 4X specifications, and is resistant to sand, debris and the elements. The large numeric pad on the SLK-102-461 allows for easy data entry, while the robust polycarbonate case is durable in the roughest of environments. Other features also include red LED backlit keys for nighttime use.




### Technical Specifications

Certifications	NEMA 4X UL60950, FCC Part 15 Class B
Shock	3 x 11 ms pulses of 50g on each of 3 axes
Key Switch	MATERIAL: Industrial Silicone Rubber LIFE: Greater Than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz. +/- 1.06oz (200g +/- 30g) FEEDBACK: Tactile with Mechanical Snap
Vibration	POWER SPECTRAL DENSITY: .04G/hz FREQUENCY RANGE: 20Hz-2Khz DURATION OF TEST PER AXIS: 3 hours
Compatibility	Ps/2 KEYBOARD/HULAPOINT: All Windows Operating Systems
Temperature Range	STORAGE: -40F to 194F (-40C to +90C) OPERATING: -40F to +158F (-40C to +70C)
Weight	1.5 lbs +/- 0.10 lbs (0.68 kg +/- 0.05 kg)
Warranty	1 year warranty
Dimensions	5.55" x 14.60" x 1.05" (w-h-d) 141mm x 370.9mm x 26.7mm

### Features and Benefits

- 12 Function Keys
- Military
- Compact
- Designed to meet MIL-STD-461E Specifications
- Full-Size
- Integrated HulaPointII Pointing Device

SK-102-461



**KEY SWITCH**

MATERIAL: Industrial Silicone Rubber  
 LIFE: Greater Than 10 Million Cycles  
 TRAVEL: 0.055 in.  
 ACTUATION FORCE: 7.05 oz. +/- 1.06oz (200g +/- 30g)  
 FEEDBACK: Tactile with Mechanical Snap

**TEMPERATURE RANGE**

STORAGE: -40°F to +194°F (-40°C to +90°C)  
 OPERATING: -40°F to +158°F (-40°C to +70°C)

**VIBRATION**

POWER SPECTRAL DENSITY: .04g/HZ  
 FREQUENCY RANGE: 20Hz-2Khz  
 DURATION OF TEST PER AXIS: 3 hours

**POWER**

PS2: KEYBOARD: 50mA@5V (from Keyboard port)  
 POINTER: 35mA@5V (from Mouse port)  
 USB: 85mA@5V (from CPU port)

**HUMIDITY**

100% Humidity Resistant

**SHOCK**

3 X 11 ms pulses of 50g on each of 3 axis

**WEIGHT**

1.50 lbs +/- 0.10 lbs (0.68 kg +/- 0.05 kg)

PROPRIETARY AND CONFIDENTIAL

SCALE: 1:2

Part Number: SK-102-461	Drawing Number: MKT0299	Sheet: 1 OF 1
Drawing Title: SK-102-461-MKT	Revision: 1.0	Date: 12.16.11
		TWH



Distributed by:  
 i-Tech Company LLC  
 TOLL FREE: (888) 483-2418 • EMAIL: [info@iTechLCD.com](mailto:info@iTechLCD.com) • WEB: [www.iTechLCD.com](http://www.iTechLCD.com)