

PANEL MOUNT FULLY SEALED IP66, STAINLESS STEEL MONITOR

24" Panel Mount Fully Sealed IP66, Stainless steel monitor. 1920x1080, 300nits, Tempered glass, IP67 I/O HDMI, DC9~36V input, Operating temperature: 0~70C, Rear OSD.

Design to Meet EU Directive 2014/30/EU for EMC and EMC qualification

CE certificate ABS certificate (Marine approval)

(TEST L/T: 14 weeks) (Test Fee is not included)



MODEL: SPMW2400WT-SIP

FEATURES:

- 24" FHD1080 TFT LCD with resolution up to 1920 x 1080
- IP66/IP69K/NEMA4X Waterproof, Stainless Steel Housing
- PCAP Touch Screen (Optional)

ACCESSORIES:

- IP67 DC Power cord x 1
- IP67 HDMI cable x 1

SPECIFICATIONS:

Display	Size/Panel Type	24" TFT LCD Panel
	Resolution	1920 x 1080
	Brightness (cd/m ²)	300cd/m ²
	Contrast Ratio	5000:1
	Response Time	25ms
	Backlight	LED Backlight Unit
	Colors	16.7M Colors
	Viewing Angle (H/V)	178°/178°
	Surface Hardness	7H, 5mm Tempered Glass
Touch Screen	Touch Screen Type	Resistive Touch / PCAP Touch(Optional)
	Surface Hardness	3H / 7H
Environment	Operating Temperature	0°C~70°C
	Storage Temperature	-10°C~75°C
	Humidity	5%~95% RH(Non-Condensing)
	Waterproof Rating	IP66 Waterproof
System	OSD	Menu, Auto, On/Off, Up, Down
	Available I/O Interface	HDMI, DC in
	Power Input	DC9~36V input
	Power Consumption	20W
	Certification	FCC/CE/RoHS Compliance
	Mounting	VESA 100 x 100mm; 200 x 200mm
	Dimension/Weight	664mm (W) x 448mm (H) x 60.5mm (D)/12kgs

MECHANICAL DRAWING

