

# PANEL MOUNT FULLY SEALED IP66, STAINLESS STEEL MONITOR

55" Panel Mount Fully Sealed IP66, Stainless Steel Monitor. 1920x1080, 450nits, Tempered glass, IP67 I/O HDMI, AC100~240V input, VESA mount, operating temperature: 0~50C, Rear OSD  
 Design to Meet EU Directive 2014/30/EU for EMC and EMC qualification  
 CE certificate ABS certificate (Marine approval)  
 (TEST L/T: 14 weeks) (Test Fee is not included)



## MODEL: SPMW5500WT-SIP

### FEATURES:

- 55" TFT LCD Monitor with Resolution up to 1920 x 1080
- IP66/NEMA4X Waterproof, Stainless Steel Housing
- 450nits High Brightness / 2500nits Sunlight Readable (Optional)

### ACCESSORIES:

- IP67 Power cord x 1
- IP67 HDMI cable x 1

### SPECIFICATIONS:

<b>Display</b>	Size/Panel Type	55" TFT LCD Panel
	Resolution	1920 x 1080
	Brightness (cd/m <sup>2</sup> )	450cd/m <sup>2</sup> / (Optional: 2500 cd/m <sup>2</sup> )
	Contrast Ratio	4000:1
	Response Time	6.5 ms
	Backlight	LED Backlight Unit
	Colors	1073.7M Colors
	Viewing Angle (H/V)	178°/178
	Surface Hardness	7H, Tempered Glass
<b>Touch Screen</b>	Touch Screen Type	IR / PCAP Touchscreen (Optional)
	Surface Hardness	7H (Tempered Glass)
<b>Environment</b>	Operating Temperature	0°~50°C
	Storage Temperature	-20°C~+60°C
	Humidity	5%~95% RH(Non-Condensing)
	Waterproof Rating	IP66/NEMA4X, 6 Side Waterproof
<b>System</b>	OSD	Menu, Auto, On/Off, Up, Down
	I/O Interface	HDMI x 1, AC in x 1,
	Power Input	AC100~240V Input
	Power Consumption	105W
	Certification	FCC/CE/RoHS Compliance
	Mounting	Panel Mount
	Dimension/Weight	1392mm (W) x 863mm (H) x 73.5mm (D)/62kgs

### MECHANICAL DRAWING

