

Sentry Metered CDU

C-48VD

Mid-Density Metered Power Distribution

Increasing power demands and density in the equipment cabinet requires new functionality from your cabinet PDU. The Sentry CDU product family uniquely meets these demands.


The Sentry Cabinet Power Distribution Unit (CDU) is an intelligent PDU with local LED input current monitoring, allowing network engineers to utilize the CDU's True RMS Power Monitor to precisely measure the current (in amps) that network devices are drawing on the power circuit. As new servers and devices are added to the power drop, immediately observe its impact on the cumulative current draw. This allows the engineer to safely load each circuit to its maximum allowable load capacity without the danger of overloading the power circuit.



Branch Circuit Protection

The Sentry CDU Family meets the new UL 60950-1 requirement for branch circuit protection.

Attention! The Sentry CDU products meet the above criteria by providing overcurrent protection with UL-listed Bussman SC fuses for each branch circuit.



Branch Current Monitoring

The CDU's exclusive True RMS current monitoring is critical to preventing overloads in high-density computing environments. LED digital displays on the CDU enclosure report the input current of each phase or branch circuit.



Button Mounting

All CDUs are also compatible with new button & "keyhole" style mounting for cabinets. Several cabinet manufacturers are now using this method for installing power distribution units in the cabinet.

Cabinet Power Distribution

Reliable single & three-phase power distribution for all the devices in your equipment cabinet. Choose a single or dual-power feed model to run all power cables to one side of the cabinet -- leaving the other side open for data cable management



Model	Available Input Voltages	Power Inlets	Outlets	Dimensions
C-48VD1-C20	100-120V 50-60Hz	IEC 60320/C20 Power Inlet	(48) NEMA L5-20R	54" x 3.5" x 2.25"
C-48VD1-L530	100-120V 50-60Hz	NEMA L5-30P Cordset, 10'	(48) NEMA L5-20R	54" x 3.5" x 2.25"
C-48VD2-C20	208-240V 60Hz	IEC 60320/C20 Power Inlet	(48) IEC 60320/C13	54" x 3.5" x 2.25"
C-48VD2-L630	208-240V 60Hz	NEMA L6-30P Cordset, 10'	(48) IEC 60320/C13	54" x 3.5" x 2.25"
C-48VDE-C20	230V 50/60Hz	IEC 60320/C20 Power Inlet	(48) IEC 60320/C13	54" x 3.5" x 2.25"

Standards

- > CTUVus – UL 60950-1-2003
- > CAN/CSA 22.2 No.60950-1:2003
- > TUV_GS – EN60950-1:2001

Power Cord Options

- > PTCORD-1 IEC 60320/C19 - NEMA L6-20P (20A Twist-Lock) 10'
- > PTCORD-2 IEC 60320/C19 - Schuko 10'
- > PTCORD-3 IEC 60320/C19 - IEC 60309 (BS4343, CEE17) 16/20A Blue (UK Commando) 10'
- > PTCORD-4 IEC 60320/C19 - BS1363 13A (UK) 10'
- > PTCORD-5 IEC 60320/C19 - 5-15P (15A Straight-Blade) 10'
- > PTCORD-6 IEC 60320/C19 - 5-20P (20A Straight-Blade) 10'
- > PTCORD-7 IEC 60320/C19 - L5-20P (20A Twist-Lock) 10'
- > PT-ADP-C19 Cable mount IEC 60320/C19 Connector