

9-inch 3GSDI & HDMI LCD Monitor



Model: SW0890SD



Features

- 9-inch, 1280x800 Resolution
- LCD protective glass
- 3G/HD/SD-SDI, HDMI, Composite video input
- 3G/HD/SD-SDI, HDMI, Composite video loop through output
- SDI and HDMI embedded audio output via 3.5mm earphone socket
- Underscan / Overscan switch
- Safe area markers
- Canon DSLR scale zoom-in
- Video flip
- Customer editable video TITLE
- V-mount / Gold mount option
- Snap-on DV mounts option

Introduction

The SW0890SD is a 9-inch 3G/HD/SD-SDI/HDMI on-camera monitor with 1280 x 800 resolution and 700:1 contrast. It has front & rear dual TALLY lights, zoom-in, video flip, customer editable video title, and safety mark display.

The monitor accepts 1 3G/HD/SD-SDI, 1 HDMI, 1 Composite video, 1 stereo audio input, and has 1 3G/HD/SD-SDI, 1 HDMI and 1 Composite video loop through output.

It's powered via a 4-pin XLR 6.5-17V DC connector or V-mount / Gold-mount / Snap-on DV battery mounts.

Simple Package includes:



Cold shoe / Screw Head



Sun Hood



Battery mount



LCD Protector



4-pin XLR AC-DC adapter

Luxury Package has additional:



HDMI cable with mini HDMI adaptor



D-tap to 4-pin XLR cable



Pan-tilt arm trestle (screw mount)



Carrying case



9-inch 3GSDI & HDMI LCD Monitor

Specifications

LCD Performance		
Size	9.0 inches	
Resolution	1280xRGBx800	
Display area	194x121mm	
Aspect ratio	16:9/4:3	
Color system	NTSC/PAL	
Brightness	250cd/m2	
Contrast	700:1	
Color	16.77 million colors	
Viewing angle	H/V:140/120	
Input and Output		
Input	1 BNC	(1) 3G/HD/SD-SDI in
	1 BNC	(1) Composite in
	1 HDMI	(1) HDMI in
	2 RCA	L/R stereo audio in
Output	1 BNC	(1) 3G/H D/SD-SDI loop through out
	1 BNC	(1) Composite loop through out
	1 HDMI	(1) HDMI loop through out
Video Format		
SDI	SMPTE-425M	1080p (60 / 59.94 / 50)
	SMPTE-274M	1080i (60/59.94/50)
		1080p (30 / 29.97 / 25 / 24 / 23.98)
	SMPTE-296M	720p (60 / 59.94 / 50)
	SMPTE-125M	480i (59.94)
ITU-R BT.656	576i (50)	
HDMI	480I / 576I / 480P / 576P	
	1080i (60 / 59.94 / 50)	
	720p (60 / 59.94 / 50)	
	1080p (60 / 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98)	
Composite	PAL/NTSC	
General		
Working voltage	DC/Battery 6.5V-17V	
Power consumption	<16W	
Working temperature	0°C — +40C	
Working humidity	10% ~90%	
Storage temperature	-15 C — +60 C	
Storage humidity	10% —90%	
Dimensions	236x171x48mm	
Net weight	970g	